

TEST REPORT

EUT Number: 61-570

Equipment Under Test: Air Conditioner

Trade Name: Toshiba

Model: RAS-5M34U2AVG-E (Outdoor) and RAS-B24PKVSG-E+
RAS-M13PKVPG-E+RAS-M13U2MUVG-E+RAS-B10U2FVG-E+
RAS-M07U2DVG-E (Indoor unit) is representative for testing.
(Please see page 9 for product Information)

Serial Number: -

Reference Number: -

Manufactured by: Toshiba Carrier (Thailand) Co., Ltd.

Customer: Toshiba Carrier (Thailand) Co., Ltd.

Address: 144/9 Moo.5, Bangkadi Industrial Park,
Tivanon Rd., T.Bangkadi, A.Muang, Pathumtani 12000

Receipt Date: 9 March 2018

Date of Test: 19, 22, 27 - 28 March 2018

Issued Date of Report: 4 April 2018

Approved by



MR. Anake Meemoosor

Operation Manager

CONTENTS

1 SUMMARY OF TESTING	3
2 TEST PLAN AND DEVIATIONS FROM STANDARD	5
2.1 TEST PLAN	5
2.2 DEVIATIONS FROM STANDARD	5
3 TEST CONDITIONS	6
3.1 OPERATION MODE	6
3.2 UNCERTAINTY APPLICATION	6
3.3 EQUIPMENT CLASSIFICATIONS	8
3.4 PROTECTION CLASSIFICATIONS	8
3.5 PERFORMANCE CRITERIA OF TEST SPECIFICATION	8
3.6 EUT FUNCTION MONITORING	8
4 TEST SYSTEM CONFIGURATION	8
4.1 EUT EXERCISE SOFTWARE	8
4.2 EUT MODIFICATIONS	8
5 EUT DESCRIPTION	9
5.1 EUT SPECIFICATION	9
5.2 EUT CONFIGURATION	11
5.3 PERIPHERALS DESCRIPTION	12
5.4 CABLES DESCRIPTION	12
6 TEST SETUP AND RESULT	13
6.1 TEST ITEM: CONDUCTED EMISSION	13
6.2 TEST ITEM: DISTURBANCE POWER	59
6.3 TEST ITEM: DISCONTINUOUS DISTURBANCE	75
6.4 TEST ITEM: HARMONIC EMISSION	79
6.5 TEST ITEM: VOLTAGE FLUCTUATION	85
6.6 TEST ITEM: ELECTROSTATIC DISCHARGE	88
6.7 TEST ITEM: ELECTRICAL FAST TRANSIENT	92
6.8 TEST ITEM: SURGE	95
6.9 TEST ITEM: CONDUCTED IMMUNITY	98
6.10 TEST ITEM: VOLTAGE DIPS	101

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

1 SUMMARY OF TESTING

This product was tested and complied according to following specification standards:

EN55014-1 Electromagnetic compatibility-Requirements for household appliances, electric tool and similar apparatus Part1: Emission.

EN55014-2 Electromagnetic compatibility-Requirements for household appliances, electric tool and similar apparatus Part2: Immunity-Product family standard.

EN 61000-3-12 Electromagnetic compatibility (EMC) - Part 3-12: Limits - Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current >16 A and 75 A per phase

EN61000-3-11 Electromagnetic compatibility (EMC) - Part 3-11: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems - Equipment with rated current 75 A and subject to conditional connection

Test Item	Test Specification	Test Method	Result
Conducted Emission	EN55014-1:2017 Table 1 Column 2,3	EN55014-1:2017	PASS
Disturbance Power	EN55014-1:2017 Table 2 Column 2,3	EN55014-1:2017	PASS
Discontinuous disturbance	EN55014-1:2017 Table 1 Column 2	EN55014-1:2017	PASS
Harmonic Emission	EN 61000-3-12:2012	EN 61000-3-12:2012	PASS
Voltage Fluctuation	EN 61000-3-11:2001	EN 61000-3-11:2001	PASS
Electrostatic Discharge	EN55014-2:2015, Table 1, 8kV air, 4kV contact, Criterion B	IEC61000-4-2:2008 (Ed2.0)	PASS
Electrical Fast Transient	EN55014-2:2015, Table 4, 1kV 5/50ns 5kHz, Criterion B	IEC61000-4-4:2012 (Ed2.0)	PASS
	EN55014-2:2015, Table 2, 0.5kV 5/50ns 5kHz, Criterion B		
Surge	EN55014-2:2015, Table 12, 1.2/50us, 2kV CM, 1kV DM, Criterion B	IEC61000-4-5:2014 (Ed2.0)	PASS

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Test Item	Test Specification	Test Method	Result
Conducted Immunity	EN55014-2:2015, Table 7, 0.15MHz to 230 MHz, 3V 1KHz 80% AM Criterion A	IEC61000-4-6:2013 (Ed 3.0)	PASS
	EN55014-2:2015, Table 5, 0.15MHz to 230 MHz, 1V 1KHz 80% AM Criterion A		
Voltage Dips	EN55014-2:2015, Table 13, Dip 60% 10P, Dip30% 25P, Interrupt 0.5P, Criterion C	IEC61000-4-11:2004 (Ed2.0)	PASS

Note: -

2 TEST PLAN AND DEVIATIONS FROM STANDARD

2.1 Test Plan

No.	Test Item	Rated voltage	Mode	Test Port	Test Specification
1	Conducted Emission	220-240 V 50 Hz	A,D	AC Main	EN55014-1:2017 Table 1 Column 2,3
2	Disturbance Power	220-240 V 50 Hz	A,D	AC Main	EN55014-1:2017 Table 2 Column 2,3
3	Discontinuous disturbance	220-240 V 50 Hz	A,D	AC Main	EN55014-1:2017 Table 1 Column 2
4	Harmonic Emission	220-240 V 50 Hz	A	AC Main	EN 61000-3-12:2012
5	Voltage Fluctuation	220-240 V 50 Hz	C	AC Main	EN 61000-3-11:2001
6	Electrostatic Discharge	220-240 V 50 Hz	E	Enclosure	EN55014-2:2015, Table 1, 8kV air, 4kV contact, Criterion B
7	Electrical Fast Transient	220-240 V 50 Hz	E	AC Main	EN55014-2:2015, Table 4, 1kV 5/50ns 5kHz, Criterion B
				Control Line.	EN55014-2:2015, Table 2, 0.5kV 5/50ns 5kHz, Criterion B
8	Surge	220-240 V 50 Hz	E	AC Main	EN55014-2:2015, Table 12, 1.2/50us, 2kV CM, 1kV DM, Criterion B
9	Conducted Immunity	220-240 V 50 Hz	E	AC Main	EN55014-2:2015, Table 7, 0.15MHz to 230 MHz, 3V 1KHz 80% AM Criterion A
				Control line.	EN55014-2:2015, Table 5, 0.15MHz to 230 MHz, 1V 1KHz 80% AM Criterion A
10	Voltage Dips	220-240 V 50 Hz	E	AC Main	EN55014-2:2015, Table 13, Dip 60% 10P, Dip30% 25P, Interrupt 0.5P, Criterion C

2.2 Deviations from standard

-

3 TEST CONDITIONS

3.1 Operation Mode

- A: Normal operation in cooling mode set temperature to 17°C and set fan speed to maximum.
- B: Normal operation in cooling mode set temperature to 17°C and change fan speed between low and high.
- C: The air temperature shall be controlled by changing the time interval every 10 minutes of operation of the Compressor motor (ON and OFF every 10 minutes).
- D: Normal operation in heating mode set temperature to 30°C and set fan speed to maximum.
- E: Normal operation in heating mode set temperature to 30°C and change fan speed between low and high.

Note: All of operation mode are following in clause 7.3.1.20 of EN55014-1:2017, annex C (C.12) of EN 61000-3-12:2012 and annex A (A.14) EN 61000-3-11:2001.

3.2 Uncertainty Application

3.2.1 Uncertainty application according to CISPR 16-4-2:2003 for Conducted Emission, Radiated Disturbance and Disturbance Power Testing.

Compliance or Non-Compliance with a disturbance limit was determined in the following manner

If U_{lab} is less than or equal to U_{cispr} in table 1, then:

- Compliance is deemed to occur if no measured disturbance exceeds the disturbance limit.
- Non-Compliance is deemed to occur if any measured disturbance exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} in table 1, then:


- Compliance is deemed to occur if no measured disturbance, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.
- Non-Compliance is deemed to occur if any measured disturbance, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Table 1 – Values of U_{cispr}

Abbreviation	Testing system	Frequency range	U_{lab}	U_{cispr}	$U_{lab} - U_{cispr}$
CE	Conducted Emission	9 kHz - 150 kHz	2.88	4.00	-1.12
CE	Conducted Emission	150 kHz - 30 MHz	3.51	3.60	-0.09
RE	Radiated Disturbance	30 MHz – 1000 MHz	4.80	5.20	-0.40
PE	Disturbance Power	30 MHz – 300 MHz	2.42	4.50	-2.08


This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

3.2.2 Uncertainty Application according to LAB 34 Edition 1 (Figure 1) for other testing system.



3.2.3 Uncertainty Application for immunity testing.

Uncertainty of each test systems are applied for compliance with related standard according to LAB 34 Edition 1 (Figure 3)



This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

3.3 Equipment Classifications

Class A for EN61000-3-12.

3.4 Protection Classifications

Class I.

3.5 Performance Criteria of Test Specification

Function	Criteria	During The Test	After The Test
Fan speed	A	The fan speed can change.	The fan speed can change.
	B	The fan speed can change delay.	The fan speed can change.
	C	The fan speed cannot change.	The fan speed cannot change. (before reset) The fan speed can change. (after reset)
Display	A	The display can show latest status.	The display can show latest status.
	B	The display cannot show latest status (Such as LCD displays dimming, brightening, disappearing or flashing)	The display cannot show latest status but can self recover initial state.
	C	The display cannot show latest status (Such as LCD displays dimming, brightening, disappearing or flashing)	The display cannot show latest status but can recover initial state by resetting.

3.6 EUT Function Monitoring

The specific phenomena are monitored by display and fan speed.

4 TEST SYSTEM CONFIGURATION

4.1 EUT Exercise Software

-

4.2 EUT Modifications

-

5 EUT DESCRIPTION

5.1 EUT Specification

Rated voltage	220-240 V / 50 Hz
Input Current/Power	≥16 A
Clock/Oscillator	-

- The appliance is a split type air conditioner consisting of indoor and outdoor part.
- It provides cooling / heating mode of operation.
- The refrigerant of R32 is used in this air conditioner.
- The main power is supplied by a single-phase, 3-pole power supply cable.
- Outdoor and indoor parts are connected by interconnection cable.
- The indoor part is equipped with an infrared wireless battery powered remote control unit and wired remote controller.

List of models:

Indoor Unit

Type	New model Name (-E)	New Model (-TR)	Fan motor	PCB	Input	
Duct	RAS-M07U2DVG-E	RAS-M07U2DVG-TR	ICF-340WD94-3, -4	MCC-1643	80 W	
	RAS-M10U2DVG-E	RAS-M10U2DVG-TR				
	RAS-M13U2DVG-E	RAS-M13U2DVG-TR			100 W	
	RAS-M16U2DVG-E	RAS-M16U2DVG-TR				
	RAS-M22U2DVG-E	RAS-M22U2DVG-TR				114 W
	RAS-M24U2DVG-E	RAS-M24U2DVG-TR				119 W
Console	RAS-B10U2FVG-E	RAS-B10U2FVG-TR	ICF-340-41-1	MCC-5068	50 W	
	RAS-B13U2FVG-E	RAS-B13U2FVG-TR				
	RAS-B18U2FVG-E	RAS-B18U2FVG-TR				
Compact 4 Way Cassette	RAS-M10U2MUVG-E	RAS-M10U2MUVG-TR	ICF-340D60-1	MCC-1643	65 W	
	RAS-M13U2MUVG-E	RAS-M13U2MUVG-TR				
	RAS-M16U2MUVG-E	RAS-M16U2MUVG-TR				
Hi-wall	RAS-B22PKVSG-E	RAS-B22PKVSG-TR	ICF-340-30-6	WP-038	45 W	
	RAS-B24PKVSG-E	RAS-B24PKVSG-TR	MF-340-30-1RT		50 W	

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Outdoor Unit

	New model Name (-E)	New Model (-TR)	Fan motor	PCB	Input	Compressor
Outdoor IMS 890H	RAS-3M26U2AVG-E	RAS-3M26U2AVG-TR	ICF-280-	MCC-	3.80kW	DX220A2T-
	RAS-4M27U2AVG-E	RAS-4M27U2AVG-TR	A60-1	1571	3.90kW	20L
	RAS-5M34U2AVG-E	RAS-5M34U2AVG-TR	WDF-340- A100-1	& WP- 041	4.40kW	DX270A2T- 20L

Note: The last suffix letters in model name shows export to Europe and turkey:

-E indicates for export to Europe and -TR indicates for export to turkey

5.2 EUT Configuration




FIGURE 1 - EUT Configuration.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

5.3 Peripherals Description

Diagram	Description	Trade Name	Model
A	Indoor	-	RAS-B24PKVSG-E+RAS-M13U2MUVG-E+ RAS-B10U2FVG-E+RAS-M07U2DVG-E+ RAS-M13PKVPG-E
B	Outdoor	-	RAS-5M34U2AVG-E

5.4 Cables Description

Ref	Cable Type	Shield	Length (meters)	Ferrite	Connector	Connection Point 1	Connection Point 2
1	AC Power line	No	1	No	AC	EUT	AC Supply
2	AC Power line	No	5	No	AC	Indoor U.	Outdoor U.

6 TEST SETUP AND RESULT

6.1 Test Item: Conducted Emission

6.1.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
EMI Test Receiver	Rohde & Schwarz	ESU26	100572	DKD	26-05-19
LISN	TESEQ	NNB52	36109	NIMT	01-02-19

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: ±3.51 dB

Ñ Test Location: SR 2

Ñ Test Environment

Cooling Mode Temperature: 30 ±5(°C)	27	Cooling Mode Humidity (%)	52
Heating Mode Temperature :15 ± 5(°C)	20	Heating Mode Humidity (%)	56

Ñ Test Setup Description

The disturbance voltage at the main terminals testing measurements were performed with the EMI receiver to observe the emission characteristics and to identify the frequency of emission that had the highest amplitude related to the EUT configuration for the disturbance voltage at the main terminals testing.

The EUT was placed on an 10 cm from ground plane in the Shield room. The power line of the EUT was connected to the LISN, which was located in the Test area. The EMI receiver measured the noise signals from the EUT. The testing method and the EUT setup were performed according to EN55014-1:2017. The EUT configuration for the disturbance voltage at the main terminals testing is shown in FIGURE 2 and 3, respectively.

Test Picture




FIGURE 2 - The setup diagram.





FIGURE 3 - The test setup picture

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

● Test Result.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Neutron.




Measurement Result of Quasi-Peak and Average Detector.

--- N Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.16194	47.6	39.0	10.1	57.7	49.1	65.4	58.2	7.7	9.1
2	0.19074	45.7	38.7	10.1	55.8	48.8	64.0	56.4	8.2	7.6
3	0.24966	41.8	33.8	10.1	51.9	43.9	61.8	53.5	9.9	9.6
4	0.3335	40.9	33.4	10.1	51.0	43.5	59.4	50.4	8.4	6.9
5	0.78319	44.2	30.9	10.1	54.3	41.0	56.0	46.0	1.7	5.0
6	0.79606	44.6	31.0	10.1	54.7	41.1	56.0	46.0	1.3	4.9
7	0.81196	44.8	30.4	10.1	54.9	40.5	56.0	46.0	1.1	5.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Test Result for Line1



Measurement Result of Quasi-Peak and Average Detector.


--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15335	48.8	41.2	10.1	58.9	51.3	65.8	58.8	6.9	7.5
2	0.16015	47.0	39.1	10.1	57.1	49.2	65.5	58.3	8.4	9.1
3	0.1998	44.1	37.3	10.1	54.2	47.4	63.6	55.9	9.4	8.5
4	0.3353	40.0	33.3	10.1	50.1	43.4	59.3	50.3	9.2	6.9
5	0.78561	43.0	29.9	10.1	53.1	40.0	56.0	46.0	2.9	6.0
6	0.79856	43.2	30.8	10.1	53.3	40.9	56.0	46.0	2.7	5.1
7	0.8107	42.8	29.0	10.1	52.9	39.1	56.0	46.0	3.1	6.9

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. 1




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---											
No.	Frequency	Reading	Reading	c.f	Result	Result	Limit	Limit	Margin	Margin	
	[MHz]	QP	CAV		QP	CAV	QP	AV	QP	CAV	
		[dB (µV)]	[dB (µV)]	[dB]	[dB (µV)]	[dB (µV)]	[dB (µV)]	[dB (µV)]	[dB]	[dB]	
1	0.2034	31.0	23.9	30.3	61.3	54.2	80.0	70.0	18.7	15.8	
2	0.29564	33.1	27.0	30.3	63.4	57.3	80.0	70.0	16.6	12.7	
3	0.33605	36.2	29.8	30.3	66.5	60.1	80.0	70.0	13.5	9.9	
4	0.38691	34.7	28.0	30.3	65.0	58.3	80.0	70.0	15.0	11.7	
5	0.51236	27.1	19.2	30.3	57.4	49.5	74.0	64.0	16.6	14.5	
6	0.71993	23.6	17.5	30.3	53.9	47.8	74.0	64.0	20.1	16.2	

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. 2



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.26731	34.5	27.3	30.3	64.8	57.6	80.0	70.0	15.2	12.4
2	0.30631	33.6	27.5	30.3	63.9	57.8	80.0	70.0	16.1	12.2
3	0.34408	34.8	28.4	30.3	65.1	58.7	80.0	70.0	14.9	11.3
4	0.40044	34.2	27.0	30.3	64.5	57.3	80.0	70.0	15.5	12.7
5	0.47116	29.4	21.8	30.3	59.7	52.1	80.0	70.0	20.3	17.9
6	0.51463	27.4	19.0	30.3	57.7	49.3	74.0	64.0	16.3	14.7
7	0.54264	27.1	18.6	30.3	57.4	48.9	74.0	64.0	16.6	15.1

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. 3



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15335	31.9	17.3	30.3	62.2	47.6	80.0	70.0	17.8	22.4
2	0.1654	30.6	16.8	30.3	60.9	47.1	80.0	70.0	19.1	22.9
3	0.17611	30.3	16.5	30.3	60.6	46.8	80.0	70.0	19.4	23.2
4	0.18291	26.0	18.1	30.3	56.3	48.4	80.0	70.0	23.7	21.6
5	0.3284	31.2	25.6	30.3	61.5	55.9	80.0	70.0	18.5	14.1
6	0.3788	30.8	25.1	30.3	61.1	55.4	80.0	70.0	18.9	14.6
7	0.40042	30.1	24.0	30.3	60.4	54.3	80.0	70.0	19.6	15.7

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. G



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	4.12545	22.5	20.3	30.3	52.8	50.6	74.0	64.0	21.2	13.4
2	4.20046	23.0	20.9	30.3	53.3	51.2	74.0	64.0	20.7	12.8
3	4.27628	21.1	16.1	30.3	51.4	46.4	74.0	64.0	22.6	17.6
4	5.02409	15.9	10.5	30.3	46.2	40.8	74.0	64.0	27.8	23.2
5	7.23437	25.4	20.5	30.3	55.7	50.8	74.0	64.0	18.3	13.2
6	21.35735	26.6	21.3	30.4	57.0	51.7	74.0	64.0	17.0	12.3
7	21.74741	28.8	23.4	30.4	59.2	53.8	74.0	64.0	14.8	10.2
8	22.13736	29.2	24.2	30.4	59.6	54.6	74.0	64.0	14.4	9.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. 1



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15618	30.8	24.2	30.3	61.1	54.5	80.0	70.0	18.9	15.5
2	0.20094	32.3	24.8	30.3	62.6	55.1	80.0	70.0	17.4	14.9
3	0.25965	34.1	27.2	30.3	64.4	57.5	80.0	70.0	15.6	12.5
4	0.26949	35.2	27.6	30.3	65.5	57.9	80.0	70.0	14.5	12.1
5	0.32893	35.0	28.7	30.3	65.3	59.0	80.0	70.0	14.7	11.0
6	0.38562	35.2	27.9	30.3	65.5	58.2	80.0	70.0	14.5	11.8
7	0.44406	30.9	22.6	30.3	61.2	52.9	80.0	70.0	18.8	17.1
8	19.69863	22.1	17.4	30.4	52.5	47.8	74.0	64.0	21.5	16.2
9	21.98967	28.2	23.2	30.4	58.6	53.6	74.0	64.0	15.4	10.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. 2



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.31756	35.8	28.8	30.3	66.1	59.1	80.0	70.0	13.9	10.9
2	0.35287	33.4	27.2	30.3	63.7	57.5	80.0	70.0	16.3	12.5
3	0.26588	34.8	27.5	30.3	65.1	57.8	80.0	70.0	14.9	12.2
4	0.38175	35.3	27.9	30.3	65.6	58.2	80.0	70.0	14.4	11.8
5	0.15788	30.1	23.6	30.3	60.4	53.9	80.0	70.0	19.6	16.1
6	0.20873	29.9	23.3	30.3	60.2	53.6	80.0	70.0	19.8	16.4
7	0.53826	27.2	18.3	30.3	57.5	48.6	74.0	64.0	16.5	15.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. 3




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15305	28.9	17.6	30.3	59.2	47.9	80.0	70.0	20.8	22.1
2	0.16534	27.5	16.0	30.3	57.8	46.3	80.0	70.0	22.2	23.7
3	0.17074	26.9	16.3	30.3	57.2	46.6	80.0	70.0	22.8	23.4
4	0.26718	29.3	21.8	30.3	59.6	52.1	80.0	70.0	20.4	17.9
5	0.33416	31.6	24.8	30.3	61.9	55.1	80.0	70.0	18.1	14.9
6	0.34483	29.6	23.3	30.3	59.9	53.6	80.0	70.0	20.1	16.4
7	0.37778	29.9	22.8	30.3	60.2	53.1	80.0	70.0	19.8	16.9
8	0.30867	28.6	22.4	30.3	58.9	52.7	80.0	70.0	21.1	17.3
9	7.24289	22.6	17.3	30.3	52.9	47.6	74.0	64.0	21.1	16.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. G




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB (µV)]	[dB (µV)]	[dB]	[dB (µV)]	[dB (µV)]	[dB (µV)]	[dB (µV)]	[dB]	[dB]
1	4.20167	22.9	20.9	30.3	53.2	51.2	74.0	64.0	20.8	12.8
2	7.15127	23.0	18.2	30.3	53.3	48.5	74.0	64.0	20.7	15.5
3	7.23541	23.6	18.5	30.3	53.9	48.8	74.0	64.0	20.1	15.2
4	7.3102	22.5	17.5	30.3	52.8	47.8	74.0	64.0	21.2	16.2
5	19.8138	22.3	17.4	30.4	52.7	47.8	74.0	64.0	21.3	16.2
6	21.77839	28.9	23.6	30.4	59.3	54.0	74.0	64.0	14.7	10.0
7	22.0551	29.0	24.0	30.4	59.4	54.4	74.0	64.0	14.6	9.6
8	22.57495	27.0	21.8	30.4	57.4	52.2	74.0	64.0	16.6	11.8

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. 1




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15109	31.7	25.1	30.3	62.0	55.4	80.0	70.0	18.0	14.6
2	0.16434	29.5	23.1	30.3	59.8	53.4	80.0	70.0	20.2	16.6
3	0.27288	35.0	27.6	30.3	65.3	57.9	80.0	70.0	14.7	12.1
4	0.320	36.0	29.0	30.3	66.3	59.3	80.0	70.0	13.7	10.7
5	0.3345	36.2	29.4	30.3	66.5	59.7	80.0	70.0	13.5	10.3
6	0.36249	33.6	27.4	30.3	63.9	57.7	80.0	70.0	16.1	12.3
7	0.38675	34.8	27.4	30.3	65.1	57.7	80.0	70.0	14.9	12.3
8	6.2804	24.2	18.4	30.3	54.5	48.7	74.0	64.0	19.5	15.3
9	7.3453	23.5	16.7	30.3	53.8	47.0	74.0	64.0	20.2	17.0
10	21.86015	29.1	24.0	30.4	59.5	54.4	74.0	64.0	14.5	9.6

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. 2



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.20094	32.7	25.1	30.3	63.0	55.4	80.0	70.0	17.0	14.6
2	0.24919	32.8	25.6	30.3	63.1	55.9	80.0	70.0	16.9	14.1
3	0.26552	34.9	27.7	30.3	65.2	58.0	80.0	70.0	14.8	12.0
4	0.31651	35.6	28.5	30.3	65.9	58.8	80.0	70.0	14.1	11.2
5	0.34323	34.7	28.2	30.3	65.0	58.5	80.0	70.0	15.0	11.5
6	0.39695	33.3	26.0	30.3	63.6	56.3	80.0	70.0	16.4	13.7
7	0.44907	30.3	22.2	30.3	60.6	52.5	80.0	70.0	19.4	17.5
8	0.50722	28.0	18.9	30.3	58.3	49.2	74.0	64.0	15.7	14.8
9	7.24688	24.4	19.2	30.3	54.7	49.5	74.0	64.0	19.3	14.5
10	21.8606	29.1	24.1	30.4	59.5	54.5	74.0	64.0	14.5	9.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. 3




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15392	36.6	18.4	30.3	66.9	48.7	80.0	70.0	13.1	21.3
2	0.16229	35.3	16.8	30.3	65.6	47.1	80.0	70.0	14.4	22.9
3	0.16695	34.8	17.4	30.3	65.1	47.7	80.0	70.0	14.9	22.3
4	0.18234	32.1	17.7	30.3	62.4	48.0	80.0	70.0	17.6	22.0
5	0.26439	30.3	22.9	30.3	60.6	53.2	80.0	70.0	19.4	16.8
6	0.342	32.1	25.5	30.3	62.4	55.8	80.0	70.0	17.6	14.2
7	0.40237	31.4	24.3	30.3	61.7	54.6	80.0	70.0	18.3	15.4
8	3.38109	19.6	14.0	30.3	49.9	44.3	74.0	64.0	24.1	19.7
9	7.26557	23.1	17.6	30.3	53.4	47.9	74.0	64.0	20.6	16.1
10	19.60087	24.3	19.2	30.4	54.7	49.6	74.0	64.0	19.3	14.4
11	22.34869	28.8	23.9	30.4	59.2	54.3	74.0	64.0	14.8	9.7

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. G




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.24671	8.2	4.3	30.3	38.5	34.6	80.0	70.0	41.5	35.4
2	0.76471	13.5	2.7	30.3	43.8	33.0	74.0	64.0	30.2	31.0
3	0.98102	14.1	10.4	30.3	44.4	40.7	74.0	64.0	29.6	23.3
4	4.19507	22.5	20.7	30.3	52.8	51.0	74.0	64.0	21.2	13.0
5	4.945	18.1	12.7	30.3	48.4	43.0	74.0	64.0	25.6	21.0
6	7.15155	24.0	19.1	30.3	54.3	49.4	74.0	64.0	19.7	14.6
7	19.63445	23.6	18.7	30.4	54.0	49.1	74.0	64.0	20.0	14.9
8	21.77962	29.8	24.8	30.4	60.2	55.2	74.0	64.0	13.8	8.8

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. 1



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15222	32.2	25.6	30.3	62.5	55.9	80.0	70.0	17.5	14.1
2	0.27062	35.7	28.1	30.3	66.0	58.4	80.0	70.0	14.0	11.6
3	0.31984	36.0	28.9	30.3	66.3	59.2	80.0	70.0	13.7	10.8
4	0.35511	33.2	26.9	30.3	63.5	57.2	80.0	70.0	16.5	12.8
5	0.38562	34.7	27.3	30.3	65.0	57.6	80.0	70.0	15.0	12.4
6	0.5145	27.9	18.9	30.3	58.2	49.2	74.0	64.0	15.8	14.8
7	0.66838	23.2	16.5	30.3	53.5	46.8	74.0	64.0	20.5	17.2
8	6.28493	23.5	18.1	30.3	53.8	48.4	74.0	64.0	20.2	15.6
9	7.39653	24.0	16.1	30.3	54.3	46.4	74.0	64.0	19.7	17.6

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. 2



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.2015	32.8	25.1	30.3	63.1	55.4	80.0	70.0	16.9	14.6
2	0.26795	35.6	27.8	30.3	65.9	58.1	80.0	70.0	14.1	11.9
3	0.33463	36.2	29.4	30.3	66.5	59.7	80.0	70.0	13.5	10.3
4	0.38062	35.1	27.8	30.3	65.4	58.1	80.0	70.0	14.6	11.9
5	0.39761	33.6	26.1	30.3	63.9	56.4	80.0	70.0	16.1	13.6
6	3.38022	21.0	14.9	30.3	51.3	45.2	74.0	64.0	22.7	18.8
7	4.12399	22.9	19.7	30.3	53.2	50.0	74.0	64.0	20.8	14.0
8	6.28017	25.1	19.0	30.3	55.4	49.3	74.0	64.0	18.6	14.7
9	7.38055	25.1	17.4	30.3	55.4	47.7	74.0	64.0	18.6	16.3

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. 3




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.16404	36.9	16.4	30.3	67.2	46.7	80.0	70.0	12.8	23.3
2	0.17035	36.8	17.6	30.3	67.1	47.9	80.0	70.0	12.9	22.1
3	0.1863	35.5	17.1	30.3	65.8	47.4	80.0	70.0	14.2	22.6
4	0.19192	35.3	17.6	30.3	65.6	47.9	80.0	70.0	14.4	22.1
5	0.20557	34.2	16.6	30.3	64.5	46.9	80.0	70.0	15.5	23.1
6	0.31698	29.8	22.7	30.3	60.1	53.0	80.0	70.0	19.9	17.0
7	0.46776	24.9	18.0	30.3	55.2	48.3	80.0	70.0	24.8	21.7
8	7.35642	22.0	14.5	30.3	52.3	44.8	74.0	64.0	21.7	19.2
9	19.60109	24.2	19.4	30.4	54.6	49.8	74.0	64.0	19.4	14.2
10	22.20304	29.9	25.1	30.4	60.3	55.5	74.0	64.0	13.7	8.5
11	24.478	21.0	13.1	30.4	51.4	43.5	74.0	64.0	22.6	20.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. G




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---											
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]	
1	0.750	12.7	1.8	30.3	43.0	32.1	74.0	64.0	31.0	31.9	
2	0.78207	11.1	3.2	30.3	41.4	33.5	74.0	64.0	32.6	30.5	
3	0.98119	16.5	11.9	30.3	46.8	42.2	74.0	64.0	27.2	21.8	
4	2.82527	10.2	4.8	30.3	40.5	35.1	74.0	64.0	33.5	28.9	
5	4.12193	21.4	19.7	30.3	51.7	50.0	74.0	64.0	22.3	14.0	
6	4.19699	22.9	20.9	30.3	53.2	51.2	74.0	64.0	20.8	12.8	
7	4.27148	21.8	16.8	30.3	52.1	47.1	74.0	64.0	21.9	16.9	
8	7.25008	25.2	20.0	30.3	55.5	50.3	74.0	64.0	18.5	13.7	
9	19.34063	23.1	18.6	30.4	53.5	49.0	74.0	64.0	20.5	15.0	
10	21.60219	29.5	24.4	30.4	59.9	54.8	74.0	64.0	14.1	9.2	
11	24.08708	21.2	14.8	30.4	51.6	45.2	74.0	64.0	22.4	18.8	
12	24.88457	19.9	11.9	30.4	50.3	42.3	74.0	64.0	23.7	21.7	

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. 1




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.19787	32.7	25.7	30.3	63.0	56.0	80.0	70.0	17.0	14.0
2	0.26835	35.8	28.0	30.3	66.1	58.3	80.0	70.0	13.9	11.7
3	0.3302	35.2	28.6	30.3	65.5	58.9	80.0	70.0	14.5	11.1
4	0.38192	35.1	27.7	30.3	65.4	58.0	80.0	70.0	14.6	12.0
5	0.51632	27.7	18.6	30.3	58.0	48.9	74.0	64.0	16.0	15.1
6	3.38963	20.6	12.4	30.3	50.9	42.7	74.0	64.0	23.1	21.3
7	6.28208	24.1	18.7	30.3	54.4	49.0	74.0	64.0	19.6	15.0
8	7.3633	24.7	17.9	30.3	55.0	48.2	74.0	64.0	19.0	15.8
9	21.84482	29.2	24.2	30.4	59.6	54.6	74.0	64.0	14.4	9.4
10	22.05537	29.3	24.4	30.4	59.7	54.8	74.0	64.0	14.3	9.2
11	22.21883	29.1	24.2	30.4	59.5	54.6	74.0	64.0	14.5	9.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. 2



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c. f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15688	31.6	25.0	30.3	61.9	55.3	80.0	70.0	18.1	14.7
2	0.1931	33.0	26.2	30.3	63.3	56.5	80.0	70.0	16.7	13.5
3	0.27389	34.9	27.8	30.3	65.2	58.1	80.0	70.0	14.8	11.9
4	0.31423	35.1	28.3	30.3	65.4	58.6	80.0	70.0	14.6	11.4
5	0.38345	35.1	27.7	30.3	65.4	58.0	80.0	70.0	14.6	12.0
6	0.50883	27.9	19.0	30.3	58.2	49.3	74.0	64.0	15.8	14.7
7	0.7032	23.0	16.4	30.3	53.3	46.7	74.0	64.0	20.7	17.3
8	3.35511	20.7	12.0	30.3	51.0	42.3	74.0	64.0	23.0	21.7
9	6.28381	24.6	18.7	30.3	54.9	49.0	74.0	64.0	19.1	15.0
10	7.25725	23.1	15.4	30.3	53.4	45.7	74.0	64.0	20.6	18.3
11	21.92732	29.0	24.3	30.4	59.4	54.7	74.0	64.0	14.6	9.3

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. 3




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.1519	32.0	17.8	30.3	62.3	48.1	80.0	70.0	17.7	21.9
2	0.15911	31.3	17.0	30.3	61.6	47.3	80.0	70.0	18.4	22.7
3	0.16072	30.4	16.6	30.3	60.7	46.9	80.0	70.0	19.3	23.1
4	0.17497	28.6	15.8	30.3	58.9	46.1	80.0	70.0	21.1	23.9
5	0.18121	27.5	17.2	30.3	57.8	47.5	80.0	70.0	22.2	22.5
6	0.18687	27.3	19.1	30.3	57.6	49.4	80.0	70.0	22.4	20.6
7	0.33586	33.2	26.3	30.3	63.5	56.6	80.0	70.0	16.5	13.4
8	0.40158	31.3	24.1	30.3	61.6	54.4	80.0	70.0	18.4	15.6
9	0.51369	25.4	17.3	30.3	55.7	47.6	74.0	64.0	18.3	16.4
10	0.68378	21.0	14.5	30.3	51.3	44.8	74.0	64.0	22.7	19.2
11	0.72307	20.7	14.3	30.3	51.0	44.6	74.0	64.0	23.0	19.4
12	6.2799	23.3	17.5	30.3	53.6	47.8	74.0	64.0	20.4	16.2
13	7.36147	24.5	17.9	30.3	54.8	48.2	74.0	64.0	19.2	15.8
14	21.74752	29.0	24.0	30.4	59.4	54.4	74.0	64.0	14.6	9.6
15	22.05561	29.6	24.7	30.4	60.0	55.1	74.0	64.0	14.0	8.9
16	22.2988	28.9	24.0	30.4	59.3	54.4	74.0	64.0	14.7	9.6

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. G




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.72991	12.5	2.3	30.3	42.8	32.6	74.0	64.0	31.2	31.4
2	0.75985	12.5	2.1	30.3	42.8	32.4	74.0	64.0	31.2	31.6
3	0.98079	17.2	13.1	30.3	47.5	43.4	74.0	64.0	26.5	20.6
4	2.80768	10.1	4.5	30.3	40.4	34.8	74.0	64.0	33.6	29.2
5	4.19852	22.7	20.9	30.3	53.0	51.2	74.0	64.0	21.0	12.8
6	5.01993	16.4	10.6	30.3	46.7	40.9	74.0	64.0	27.3	23.1
7	7.25088	24.9	19.8	30.3	55.2	50.1	74.0	64.0	18.8	13.9
8	19.8779	23.9	19.0	30.4	54.3	49.4	74.0	64.0	19.7	14.6
9	21.87719	30.8	26.0	30.4	61.2	56.4	74.0	64.0	12.8	7.6
10	22.1379	30.4	25.6	30.4	60.8	56.0	74.0	64.0	13.2	8.0
11	22.26736	30.5	25.4	30.4	60.9	55.8	74.0	64.0	13.1	8.2

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Neutron.




Measurement Result of Quasi-Peak and Average Detector.

--- N Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15362	48.5	41.0	10.1	58.6	51.1	65.8	58.7	7.2	7.6
2	0.16885	46.4	39.0	10.1	56.5	49.1	65.0	57.7	8.5	8.6
3	0.1897	45.8	38.8	10.1	55.9	48.9	64.0	56.5	8.1	7.6
4	0.27015	42.4	35.0	10.1	52.5	45.1	61.1	52.6	8.6	7.5
5	0.32432	41.5	34.7	10.1	51.6	44.8	59.6	50.7	8.0	5.9
6	0.5533	38.7	26.7	10.1	48.8	36.8	56.0	46.0	7.2	9.2
7	0.77744	44.3	34.6	10.1	54.4	44.7	56.0	46.0	1.6	1.3
8	0.7962	44.9	33.8	10.1	55.0	43.9	56.0	46.0	1.0	2.1
9	0.81398	44.6	31.4	10.1	54.7	41.5	56.0	46.0	1.3	4.5
10	0.91267	42.1	22.1	10.1	52.2	32.2	56.0	46.0	3.8	13.8

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Test Result for Line1



Measurement Result of Quasi-Peak and Average Detector.


--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15335	48.6	41.3	10.1	58.7	51.4	65.8	58.8	7.1	7.4
2	0.16355	46.0	38.7	10.1	56.1	48.8	65.3	58.1	9.2	9.3
3	0.19697	44.2	37.8	10.1	54.3	47.9	63.7	56.1	9.4	8.2
4	0.27062	41.6	34.3	10.1	51.7	44.4	61.1	52.6	9.4	8.2
5	0.77795	44.1	34.9	10.1	54.2	45.0	56.0	46.0	1.8	1.0
6	0.79765	44.5	33.3	10.1	54.6	43.4	56.0	46.0	1.4	2.6
7	0.81232	43.7	31.4	10.1	53.8	41.5	56.0	46.0	2.2	4.5
8	0.91088	40.4	22.9	10.1	50.5	33.0	56.0	46.0	5.5	13.0
9	1.26664	37.3	19.9	10.1	47.4	30.0	56.0	46.0	8.6	16.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. 1



Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.21567	29.9	24.0	30.3	60.2	54.3	80.0	70.0	19.8	15.7
2	0.27411	34.7	28.5	30.3	65.0	58.8	80.0	70.0	15.0	11.2
3	0.34209	36.8	30.9	30.3	67.1	61.2	80.0	70.0	12.9	8.8
4	0.37765	35.2	29.0	30.3	65.5	59.3	80.0	70.0	14.5	10.7
5	0.40601	34.1	26.9	30.3	64.4	57.2	80.0	70.0	15.6	12.8
6	0.44793	30.8	22.4	30.3	61.1	52.7	80.0	70.0	18.9	17.3
7	0.50641	28.6	19.7	30.3	58.9	50.0	74.0	64.0	15.1	14.0
8	0.67105	24.2	17.1	30.3	54.5	47.4	74.0	64.0	19.5	16.6
9	3.44239	20.5	12.1	30.3	50.8	42.4	74.0	64.0	23.2	21.6
10	4.19801	23.5	21.1	30.3	53.8	51.4	74.0	64.0	20.2	12.6
11	6.28109	23.2	18.4	30.3	53.5	48.7	74.0	64.0	20.5	15.3
12	7.24968	27.1	21.8	30.3	57.4	52.1	74.0	64.0	16.6	11.9
13	21.81261	28.6	23.4	30.4	59.0	53.8	74.0	64.0	15.0	10.2
14	22.07227	28.7	23.7	30.4	59.1	54.1	74.0	64.0	14.9	9.9
15	22.29944	29.1	24.1	30.4	59.5	54.5	74.0	64.0	14.5	9.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. 2




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.18842	32.9	25.7	30.3	63.2	56.0	80.0	70.0	16.8	14.0
2	0.26949	36.1	29.0	30.3	66.4	59.3	80.0	70.0	13.6	10.7
3	0.32104	36.8	29.9	30.3	67.1	60.2	80.0	70.0	12.9	9.8
4	0.33803	37.3	30.8	30.3	67.6	61.1	80.0	70.0	12.4	8.9
5	0.37655	35.6	29.4	30.3	65.9	59.7	80.0	70.0	14.1	10.3
6	0.40358	35.0	28.1	30.3	65.3	58.4	80.0	70.0	14.7	11.6
7	0.53797	27.8	19.3	30.3	58.1	49.6	74.0	64.0	15.9	14.4
8	3.47859	20.4	12.6	30.3	50.7	42.9	74.0	64.0	23.3	21.1
9	7.3133	25.2	20.0	30.3	55.5	50.3	74.0	64.0	18.5	13.7
10	19.79855	21.7	16.6	30.4	52.1	47.0	74.0	64.0	21.9	17.0
11	21.42278	26.8	21.3	30.4	57.2	51.7	74.0	64.0	16.8	12.3
12	22.25101	29.4	24.1	30.4	59.8	54.5	74.0	64.0	14.2	9.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. 3




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15795	30.4	18.9	30.3	60.7	49.2	80.0	70.0	19.3	20.8
2	0.26901	30.4	22.6	30.3	60.7	52.9	80.0	70.0	19.3	17.1
3	0.33473	32.4	26.0	30.3	62.7	56.3	80.0	70.0	17.3	13.7
4	0.38288	31.2	24.9	30.3	61.5	55.2	80.0	70.0	18.5	14.8
5	0.44633	26.3	19.1	30.3	56.6	49.4	80.0	70.0	23.4	20.6
6	0.51458	23.5	15.4	30.3	53.8	45.7	74.0	64.0	20.2	18.3
7	0.6755	18.3	11.6	30.3	48.6	41.9	74.0	64.0	25.4	22.1
8	1.08471	14.0	6.1	30.3	44.3	36.4	74.0	64.0	29.7	27.6
9	1.14629	14.5	7.4	30.3	44.8	37.7	74.0	64.0	29.2	26.3
10	7.26765	23.6	18.2	30.3	53.9	48.5	74.0	64.0	20.1	15.5
11	21.51982	27.3	21.9	30.4	57.7	52.3	74.0	64.0	16.3	11.7
12	22.00828	29.0	24.0	30.4	59.4	54.4	74.0	64.0	14.6	9.6
13	22.34927	29.5	24.4	30.4	59.9	54.8	74.0	64.0	14.1	9.2

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit A No. G




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.75221	10.2	-1.0	30.3	40.5	29.3	74.0	64.0	33.5	34.7
2	0.98087	12.7	9.7	30.3	43.0	40.0	74.0	64.0	31.0	24.0
3	2.99465	12.0	8.0	30.3	42.3	38.3	74.0	64.0	31.7	25.7
4	4.11955	21.0	19.0	30.3	51.3	49.3	74.0	64.0	22.7	14.7
5	4.19558	21.5	19.3	30.3	51.8	49.6	74.0	64.0	22.2	14.4
6	4.27065	19.2	15.1	30.3	49.5	45.4	74.0	64.0	24.5	18.6
7	7.15179	23.6	18.7	30.3	53.9	49.0	74.0	64.0	20.1	15.0
8	7.23921	21.7	16.1	30.3	52.0	46.4	74.0	64.0	22.0	17.6
9	7.31139	22.7	17.8	30.3	53.0	48.1	74.0	64.0	21.0	15.9
10	21.48713	27.5	22.2	30.4	57.9	52.6	74.0	64.0	16.1	11.4
11	21.90943	29.3	24.2	30.4	59.7	54.6	74.0	64.0	14.3	9.4
12	22.26659	23.4	16.4	30.4	53.8	46.8	74.0	64.0	20.2	17.2

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. 1



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.26269	34.9	28.6	30.3	65.2	58.9	80.0	70.0	14.8	11.1
2	0.3166	36.8	30.5	30.3	67.1	60.8	80.0	70.0	12.9	9.2
3	0.3386	37.3	31.2	30.3	67.6	61.5	80.0	70.0	12.4	8.5
4	0.38392	35.6	28.9	30.3	65.9	59.2	80.0	70.0	14.1	10.8
5	0.40465	34.6	27.7	30.3	64.9	58.0	80.0	70.0	15.1	12.0
6	0.54053	27.7	19.5	30.3	58.0	49.8	74.0	64.0	16.0	14.2
7	7.28128	23.3	17.6	30.3	53.6	47.9	74.0	64.0	20.4	16.1
8	21.73245	28.0	22.9	30.4	58.4	53.3	74.0	64.0	15.6	10.7

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. 2




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.27252	35.2	28.4	30.3	65.5	58.7	80.0	70.0	14.5	11.3
2	0.32397	36.5	30.3	30.3	66.8	60.6	80.0	70.0	13.2	9.4
3	0.33386	37.3	31.1	30.3	67.6	61.4	80.0	70.0	12.4	8.6
4	0.37939	35.8	29.3	30.3	66.1	59.6	80.0	70.0	13.9	10.4
5	0.40488	34.8	28.0	30.3	65.1	58.3	80.0	70.0	14.9	11.7
6	0.50641	28.4	19.9	30.3	58.7	50.2	74.0	64.0	15.3	13.8
7	0.54113	27.9	19.8	30.3	58.2	50.1	74.0	64.0	15.8	13.9
8	19.82935	18.5	12.6	30.4	48.9	43.0	74.0	64.0	25.1	21.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. 3




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.25825	29.1	22.3	30.3	59.4	52.6	80.0	70.0	20.6	17.4
2	0.3166	32.0	25.8	30.3	62.3	56.1	80.0	70.0	17.7	13.9
3	0.33747	32.3	26.2	30.3	62.6	56.5	80.0	70.0	17.4	13.5
4	0.37931	31.2	24.9	30.3	61.5	55.2	80.0	70.0	18.5	14.8
5	0.44123	25.6	19.0	30.3	55.9	49.3	80.0	70.0	24.1	20.7
6	7.24736	24.5	19.2	30.3	54.8	49.5	74.0	64.0	19.2	14.5
7	22.18693	29.5	24.6	30.4	59.9	55.0	74.0	64.0	14.1	9.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit B No. G



Measurement Result of Quasi-Peak and Average Detector.

```

--- Probe Phase ---


```

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.98146	12.8	9.8	30.3	43.1	40.1	74.0	64.0	30.9	23.9
2	4.1934	22.9	20.8	30.3	53.2	51.1	74.0	64.0	20.8	12.9
3	7.20094	24.3	19.2	30.3	54.6	49.5	74.0	64.0	19.4	14.5
4	19.25927	20.5	15.7	30.4	50.9	46.1	74.0	64.0	23.1	17.9
5	20.40001	22.9	17.8	30.4	53.3	48.2	74.0	64.0	20.7	15.8
6	21.78082	29.0	23.9	30.4	59.4	54.3	74.0	64.0	14.6	9.7
7	22.35007	29.5	24.6	30.4	59.9	55.0	74.0	64.0	14.1	9.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. 1



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.27232	35.2	28.4	30.3	65.5	58.7	80.0	70.0	14.5	11.3
2	0.3166	36.8	30.5	30.3	67.1	60.8	80.0	70.0	12.9	9.2
3	0.33917	37.3	31.4	30.3	67.6	61.7	80.0	70.0	12.4	8.3
4	0.37892	35.7	29.5	30.3	66.0	59.8	80.0	70.0	14.0	10.2
5	0.40148	35.0	28.1	30.3	65.3	58.4	80.0	70.0	14.7	11.6
6	0.53879	27.7	19.4	30.3	58.0	49.7	74.0	64.0	16.0	14.3
7	3.46302	21.0	13.3	30.3	51.3	43.6	74.0	64.0	22.7	20.4
8	6.32286	22.8	14.8	30.3	53.1	45.1	74.0	64.0	20.9	18.9
9	7.24972	25.4	19.8	30.3	55.7	50.1	74.0	64.0	18.3	13.9
10	21.71565	28.5	23.4	30.4	58.9	53.8	74.0	64.0	15.1	10.2

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. 2



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c. f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.2683	35.8	28.8	30.3	66.1	59.1	80.0	70.0	13.9	10.9
2	0.33869	37.4	31.3	30.3	67.7	61.6	80.0	70.0	12.3	8.4
3	0.37706	35.7	29.6	30.3	66.0	59.9	80.0	70.0	14.0	10.1
4	0.5126	28.3	20.0	30.3	58.6	50.3	74.0	64.0	15.4	13.7
5	7.10502	22.8	17.7	30.3	53.1	48.0	74.0	64.0	20.9	16.0
6	22.3497	29.2	24.3	30.4	59.6	54.7	74.0	64.0	14.4	9.3

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. 3



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c. f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.27071	30.7	23.3	30.3	61.0	53.6	80.0	70.0	19.0	16.4
2	0.33677	33.9	27.6	30.3	64.2	57.9	80.0	70.0	15.8	12.1
3	0.37722	32.8	27.0	30.3	63.1	57.3	80.0	70.0	16.9	12.7
4	0.40288	32.4	26.0	30.3	62.7	56.3	80.0	70.0	17.3	13.7
5	0.50856	26.1	18.6	30.3	56.4	48.9	74.0	64.0	17.6	15.1
6	3.48257	18.8	11.0	30.3	49.1	41.3	74.0	64.0	24.9	22.7
7	6.28085	22.7	18.1	30.3	53.0	48.4	74.0	64.0	21.0	15.6
8	7.18544	23.8	18.5	30.3	54.1	48.8	74.0	64.0	19.9	15.2
9	21.63379	28.9	23.6	30.4	59.3	54.0	74.0	64.0	14.7	10.0
10	22.17011	30.7	25.7	30.4	61.1	56.1	74.0	64.0	12.9	7.9

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit C No. G



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.75985	9.5	-0.2	30.3	39.8	30.1	74.0	64.0	34.2	33.9
2	2.76203	9.7	4.5	30.3	40.0	34.8	74.0	64.0	34.0	29.2
3	4.19603	22.3	20.4	30.3	52.6	50.7	74.0	64.0	21.4	13.3
4	7.11787	25.5	20.6	30.3	55.8	50.9	74.0	64.0	18.2	13.1
5	7.20284	23.7	18.6	30.3	54.0	48.9	74.0	64.0	20.0	15.1
6	7.2976	24.7	20.1	30.3	55.0	50.4	74.0	64.0	19.0	13.6
7	19.86201	23.2	18.3	30.4	53.6	48.7	74.0	64.0	20.4	15.3
8	21.55209	27.5	22.2	30.4	57.9	52.6	74.0	64.0	16.1	11.4
9	23.79665	21.1	15.3	30.4	51.5	45.7	74.0	64.0	22.5	18.3

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. 1



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.26392	35.0	28.5	30.3	65.3	58.8	80.0	70.0	14.7	11.2
2	0.32047	37.0	30.7	30.3	67.3	61.0	80.0	70.0	12.7	9.0
3	0.37892	35.8	29.5	30.3	66.1	59.8	80.0	70.0	13.9	10.2
4	0.53339	27.7	18.4	30.3	58.0	48.7	74.0	64.0	16.0	15.3
5	0.72087	23.5	17.2	30.3	53.8	47.5	74.0	64.0	20.2	16.5
6	7.2468	25.4	19.7	30.3	55.7	50.0	74.0	64.0	18.3	14.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. 2



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.27051	35.5	28.4	30.3	65.8	58.7	80.0	70.0	14.2	11.3
2	0.33756	37.0	30.8	30.3	67.3	61.1	80.0	70.0	12.7	8.9
3	0.3827	35.7	29.0	30.3	66.0	59.3	80.0	70.0	14.0	10.7
4	6.28374	24.7	18.6	30.3	55.0	48.9	74.0	64.0	19.0	15.1
5	7.31401	24.4	17.5	30.3	54.7	47.8	74.0	64.0	19.3	16.2
6	20.65871	23.5	18.2	30.4	53.9	48.6	74.0	64.0	20.1	15.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. 3




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.16332	35.6	15.6	30.3	65.9	45.9	80.0	70.0	14.1	24.1
2	0.17044	34.9	15.5	30.3	65.2	45.8	80.0	70.0	14.8	24.2
3	0.17375	34.5	14.7	30.3	64.8	45.0	80.0	70.0	15.2	25.0
4	0.18517	33.2	17.3	30.3	63.5	47.6	80.0	70.0	16.5	22.4
5	0.33803	31.9	26.0	30.3	62.2	56.3	80.0	70.0	17.8	13.7
6	0.35616	30.6	25.2	30.3	60.9	55.5	80.0	70.0	19.1	14.5
7	22.00772	29.7	24.7	30.4	60.1	55.1	74.0	64.0	13.9	8.9

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit D No. G



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.75729	9.5	-1.1	30.3	39.8	29.2	74.0	64.0	34.2	34.8
2	2.73542	9.4	4.2	30.3	39.7	34.5	74.0	64.0	34.3	29.5
3	4.19308	23.3	20.7	30.3	53.6	51.0	74.0	64.0	20.4	13.0
4	4.26853	21.1	15.9	30.3	51.4	46.2	74.0	64.0	22.6	17.8
5	4.11776	21.1	19.3	30.3	51.4	49.6	74.0	64.0	22.6	14.4
6	7.19926	24.0	19.0	30.3	54.3	49.3	74.0	64.0	19.7	14.7
7	22.17046	30.0	24.9	30.4	60.4	55.3	74.0	64.0	13.6	8.7
8	22.34927	23.4	15.9	30.4	53.8	46.3	74.0	64.0	20.2	17.7
9	21.81242	28.7	23.6	30.4	59.1	54.0	74.0	64.0	14.9	10.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. 1



Measurement Result of Quasi-Peak and Average Detector.


--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.25995	34.9	28.6	30.3	65.2	58.9	80.0	70.0	14.8	11.1
2	0.31934	36.9	30.5	30.3	67.2	60.8	80.0	70.0	12.8	9.2
3	0.34041	37.3	31.2	30.3	67.6	61.5	80.0	70.0	12.4	8.5
4	0.37892	35.9	29.5	30.3	66.2	59.8	80.0	70.0	13.8	10.2
5	0.51612	28.3	19.4	30.3	58.6	49.7	74.0	64.0	15.4	14.3
6	21.58526	27.3	22.0	30.4	57.7	52.4	74.0	64.0	16.3	11.6
7	22.20291	29.6	24.8	30.4	60.0	55.2	74.0	64.0	14.0	8.8

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. 2




Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.26949	35.8	28.7	30.3	66.1	59.0	80.0	70.0	13.9	11.0
2	0.31418	36.3	30.2	30.3	66.6	60.5	80.0	70.0	13.4	9.5
3	0.33643	37.2	31.0	30.3	67.5	61.3	80.0	70.0	12.5	8.7
4	0.3765	35.3	29.3	30.3	65.6	59.6	80.0	70.0	14.4	10.4
5	0.40826	33.6	26.5	30.3	63.9	56.8	80.0	70.0	16.1	13.2
6	7.35673	24.8	17.1	30.3	55.1	47.4	74.0	64.0	18.9	16.6
7	22.23411	29.0	24.1	30.4	59.4	54.5	74.0	64.0	14.6	9.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. 3



Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---										
No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.33246	33.4	27.2	30.3	63.7	57.5	80.0	70.0	16.3	12.5
2	0.38109	33.0	26.7	30.3	63.3	57.0	80.0	70.0	16.7	13.0
3	0.50965	25.8	18.4	30.3	56.1	48.7	74.0	64.0	17.9	15.3
4	0.74029	19.7	12.8	30.3	50.0	43.1	74.0	64.0	24.0	20.9
5	7.26747	24.2	17.9	30.3	54.5	48.2	74.0	64.0	19.5	15.8
6	21.68374	22.5	16.2	30.4	52.9	46.6	74.0	64.0	21.1	17.4
7	22.15403	29.1	24.2	30.4	59.5	54.6	74.0	64.0	14.5	9.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

Test Result for Probe Unit E No. G



Measurement Result of Quasi-Peak and Average Detector.

--- Probe Phase ---

No.	Frequency [MHz]	Reading QP [dB (µV)]	Reading CAV [dB (µV)]	c.f [dB]	Result QP [dB (µV)]	Result CAV [dB (µV)]	Limit QP [dB (µV)]	Limit AV [dB (µV)]	Margin QP [dB]	Margin CAV [dB]
1	0.97984	14.1	10.3	30.3	44.4	40.6	74.0	64.0	29.6	23.4
2	4.19334	23.3	20.7	30.3	53.6	51.0	74.0	64.0	20.4	13.0
3	7.11908	24.0	18.9	30.3	54.3	49.2	74.0	64.0	19.7	14.8
4	7.21679	25.7	21.1	30.3	56.0	51.4	74.0	64.0	18.0	12.6
5	7.32896	24.2	19.3	30.3	54.5	49.6	74.0	64.0	19.5	14.4
6	21.21045	25.8	20.3	30.4	56.2	50.7	74.0	64.0	17.8	13.3
7	21.6496	28.0	22.7	30.4	58.4	53.1	74.0	64.0	15.6	10.9
8	22.05633	29.6	24.6	30.4	60.0	55.0	74.0	64.0	14.0	9.0
9	22.36559	29.6	24.5	30.4	60.0	54.9	74.0	64.0	14.0	9.1
10	22.70614	27.0	22.0	30.4	57.4	52.4	74.0	64.0	16.6	11.6

Result: Pass

Tested by: Marut Hninae

6.2 Test Item: Disturbance Power

6.2.1 Test Setup

- Test Specification

See 1 and 2.1

- Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
EMI Test Receiver	Rohde & Schwarz	ESU26	100572	DKD	26-05-19
Pre-Amplifier	HP	8447FGPTH64	3113A05499	NIMT	01-02-19
Absorbing Clamp	TESEQ	AMZ41A	38694	TESEQ	06-02-19

- Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

- Test Uncertainty: ± 2.42 dB

- Test Location: SR 2

- Test Environment

Cooling Mode Temperature: $30 \pm 5(^{\circ}\text{C})$	26	Cooling Mode Humidity (%)	55
Heating Mode Temperature : $15 \pm 5(^{\circ}\text{C})$	20	Heating Mode Humidity (%)	52

- Test Setup Description

The disturbance power measurements were performed with the EMI receiver to measure the emission characteristics and to identify the frequency of emission that has the highest amplitude related to the EUT configuration for disturbance power testing. The EUT configuration, cable alignments, and EUT operation mode were determined for producing the maximum level of emissions.

The EUT was located at Shield room, which those closed to the absorbing slide bar. The power line of the EUT was fed through the absorbing clamp and ferrite clamp to the public main terminal AC as shown in FIGURE 4 and 5, respectively. The EMI receiver measured the noise signals from the EUT. The testing method and the EUT setup were performed according to EN55014-1:2017.

● Test Picture




FIGURE 4 - The setup diagram.




FIGURE 5 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.2.2 Test Result

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	30.817	60.7	48.4	-26.6	34.1	21.8	45.1	35.1	11.0	13.3
2	31.867	61.9	49.5	-26.7	35.2	22.8	45.3	35.3	10.1	12.5
3	32.800	60.3	48.4	-26.9	33.4	21.5	45.4	35.4	12.0	13.9
4	44.000	53.3	42.7	-28.8	24.5	13.9	46.7	36.7	22.3	22.8
5	47.267	56.8	46.0	-29.0	27.8	17.0	47.0	37.0	19.2	20.0
6	53.683	51.9	43.3	-29.3	22.6	14.0	47.5	37.5	24.9	23.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control A	Operation Mode	A (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	31.283	54.5	42.9	-26.6	27.9	16.3	45.2	35.2	17.3	18.9
2	32.450	47.8	38.3	-26.8	21.0	11.5	45.3	35.3	24.3	23.8
3	40.033	55.9	45.9	-28.4	27.5	17.5	46.3	36.3	18.8	18.8
4	47.967	59.7	49.4	-29.1	30.6	20.3	47.0	37.0	16.4	16.7
5	53.683	56.4	48.1	-29.3	27.1	18.8	47.5	37.5	20.4	18.7
6	64.883	52.7	45.8	-29.5	23.2	16.3	48.4	38.4	25.2	22.1

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control B	Operation Mode	A (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	32.917	53.8	44.2	-26.9	26.9	17.3	45.4	35.4	18.5	18.1
2	34.317	50.0	40.7	-27.2	22.8	13.5	45.6	35.6	22.8	22.1
3	44.117	54.1	45.3	-28.8	25.3	16.5	46.7	36.7	21.4	20.2
4	47.617	53.7	43.8	-29.0	24.7	14.8	47.0	37.0	22.3	22.2
5	53.917	50.2	39.6	-29.3	20.9	10.3	47.5	37.5	26.6	27.2
6	63.367	50.9	37.9	-29.4	21.5	8.5	48.2	38.2	26.7	29.7

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control C	Operation Mode	A (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	30.812	59.2	46.9	-26.6	32.6	20.3	45.1	35.1	12.5	14.8
2	32.029	59.6	47.9	-26.8	32.8	21.1	45.3	35.3	12.5	14.2
3	35.174	57.9	48.3	-27.3	30.6	21.0	45.7	35.7	15.1	14.7
4	45.014	59.5	48.2	-28.9	30.6	19.3	46.8	36.8	16.2	17.5
5	47.551	60.0	49.2	-29.0	31.0	20.2	47.0	37.0	16.0	16.8
6	53.638	62.0	50.0	-29.3	32.7	20.7	47.5	37.5	14.8	16.8

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control D	Operation Mode	A (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c. f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	31.217	56.3	44.6	-26.6	29.7	18.0	45.2	35.2	15.5	17.2
2	35.681	56.6	46.6	-27.5	29.1	19.1	45.8	35.8	16.7	16.7
3	36.899	57.5	47.1	-27.8	29.7	19.3	45.9	35.9	16.2	16.6
4	39.130	55.2	45.3	-28.3	26.9	17.0	46.2	36.2	19.3	19.2
5	44.203	57.2	47.3	-28.8	28.4	18.5	46.7	36.7	18.3	18.2
6	49.681	60.0	45.9	-29.2	30.8	16.7	47.2	37.2	16.4	20.5

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control E	Operation Mode	A (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (pW)]	Reading AV [dB (pW)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	32.330	55.2	44.7	-26.8	28.4	17.9	45.3	35.3	16.9	17.4
2	36.899	59.7	49.1	-27.8	31.9	21.3	45.9	35.9	14.0	14.6
3	42.174	58.2	46.9	-28.7	29.5	18.2	46.5	36.5	17.0	18.3
4	49.783	60.9	45.9	-29.2	31.7	16.7	47.2	37.2	15.5	20.5
5	53.536	58.9	47.6	-29.3	29.6	18.3	47.5	37.5	17.9	19.2
6	87.014	55.9	43.7	-29.1	26.8	14.6	49.6	39.6	22.8	25.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Remote Unit C	Operation Mode	A (See 3.1)
------------------	---------------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c. f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	34.971	65.4	52.4	-27.3	38.1	25.1	45.7	35.7	7.6	10.6
2	42.174	56.1	45.4	-28.7	27.4	16.7	46.5	36.5	19.1	19.8
3	51.000	57.3	45.5	-29.2	28.1	16.3	47.3	37.3	19.2	21.0
4	53.739	55.6	44.3	-29.3	26.3	15.0	47.5	37.5	21.2	22.5
5	65.812	46.0	34.9	-29.5	16.5	5.4	48.4	38.4	31.9	33.0
6	87.826	61.0	47.1	-29.1	31.9	18.0	49.7	39.7	17.8	21.7

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	30.817	58.6	46.6	-26.6	32.0	20.0	45.1	35.1	13.1	15.1
2	31.750	60.5	47.9	-26.7	33.8	21.2	45.2	35.2	11.4	14.0
3	32.567	61.6	49.6	-26.8	34.8	22.8	45.4	35.4	10.6	12.6
4	43.533	57.6	46.7	-28.8	28.8	17.9	46.6	36.6	17.8	18.7
5	47.617	59.9	49.0	-29.0	30.9	20.0	47.0	37.0	16.1	17.0
6	53.683	59.9	49.0	-29.3	30.6	19.7	47.5	37.5	16.9	17.8

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control A	Operation Mode	D (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (pW)]	Reading AV [dB (pW)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	31.050	56.0	44.4	-26.6	29.4	17.8	45.1	35.1	15.7	17.3
2	40.383	50.1	40.5	-28.5	21.6	12.0	46.3	36.3	24.7	24.3
3	47.617	61.4	51.4	-29.0	32.4	22.4	47.0	37.0	14.6	14.6
4	53.100	51.7	43.5	-29.3	22.4	14.2	47.5	37.5	25.1	23.3
5	59.050	53.5	47.1	-29.4	24.1	17.7	47.9	37.9	23.8	20.2
6	63.833	54.5	45.6	-29.5	25.0	16.1	48.3	38.3	23.3	22.2

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control B	Operation Mode	D (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	30.817	50.4	39.4	-26.6	23.8	12.8	45.1	35.1	21.3	22.3
2	33.267	52.9	41.8	-27.0	25.9	14.8	45.4	35.4	19.5	20.6
3	43.883	48.9	39.9	-28.8	20.1	11.1	46.7	36.7	26.6	25.6
4	47.500	58.5	48.1	-29.0	29.5	19.1	47.0	37.0	17.5	17.9
5	54.967	47.9	38.6	-29.3	18.6	9.3	47.6	37.6	29.0	28.3
6	62.667	51.7	39.6	-29.4	22.3	10.2	48.2	38.2	25.9	28.0

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control C	Operation Mode	D (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (pW)]	Reading AV [dB (pW)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	30.913	60.1	48.3	-26.6	33.5	21.7	45.1	35.1	11.6	13.4
2	32.330	59.3	47.8	-26.8	32.5	21.0	45.3	35.3	12.8	14.3
3	34.971	56.9	47.3	-27.3	29.6	20.0	45.7	35.7	16.1	15.7
4	37.203	57.4	46.8	-27.8	29.6	19.0	45.9	35.9	16.3	16.9
5	45.319	58.2	46.6	-28.9	29.3	17.7	46.8	36.8	17.5	19.1
6	47.551	60.7	49.2	-29.0	31.7	20.2	47.0	37.0	15.3	16.8
7	53.638	61.6	48.9	-29.3	32.3	19.6	47.5	37.5	15.2	17.9

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control D	Operation Mode	D (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	31.420	54.8	43.2	-26.7	28.1	16.5	45.2	35.2	17.1	18.7
2	36.188	57.5	47.1	-27.6	29.9	19.5	45.8	35.8	15.9	16.3
3	40.043	57.3	50.0	-28.4	28.9	21.6	46.3	36.3	17.4	14.7
4	44.406	57.4	47.0	-28.8	28.6	18.2	46.7	36.7	18.1	18.5
5	49.174	59.7	45.8	-29.1	30.6	16.7	47.1	37.1	16.5	20.4
6	53.942	60.1	46.0	-29.3	30.8	16.7	47.5	37.5	16.7	20.8

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Control E	Operation Mode	D (See 3.1)
------------------	-----------	----------------	-------------




Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	31.217	53.1	43.1	-26.6	26.5	16.5	45.2	35.2	18.7	18.7
2	35.681	57.4	47.3	-27.5	29.9	19.8	45.8	35.8	15.9	16.0
3	37.406	58.6	47.8	-27.9	30.7	19.9	46.0	36.0	15.3	16.1
4	40.145	58.1	47.2	-28.5	29.6	18.7	46.3	36.3	16.7	17.6
5	49.681	61.9	46.8	-29.2	32.7	17.6	47.2	37.2	14.5	19.6
6	53.739	58.7	47.4	-29.3	29.4	18.1	47.5	37.5	18.1	19.4

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	Remote Unit C	Operation Mode	D (See 3.1)
------------------	---------------	----------------	-------------



Measurement Result.

No.	Frequency [MHz]	Reading QP [dB (μV)]	Reading AV [dB (μV)]	c.f [dB]	Result QP [dB (pW)]	Result AV [dB (pW)]	Limit QP [dB (pW)]	Limit AV [dB (pW)]	Margin QP [dB]	Margin AV [dB]
1	30.304	60.3	46.6	-26.5	33.8	20.1	45.0	35.0	11.2	14.9
2	33.957	60.1	47.7	-27.1	33.0	20.6	45.5	35.5	12.5	14.9
3	34.768	61.2	48.4	-27.2	34.0	21.2	45.6	35.6	11.6	14.4
4	35.580	62.7	49.9	-27.4	35.3	22.5	45.7	35.7	10.4	13.2
5	51.203	57.8	46.3	-29.3	28.5	17.0	47.3	37.3	18.8	20.3
6	87.725	60.7	46.5	-29.1	31.6	17.4	49.7	39.7	18.1	22.3

Result: Pass

Tested by: Marut Hninae

6.3 Test Item: Discontinuous Disturbance

6.3.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
Click Analyzer	AFJ	CL55C	55040019052	UKAS	10-09-18
LISN	TESEQ	NNB52	36109	NIMT	01-02-19

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: ± 3.70 dB

Ñ Test Location: SR 2

Ñ Test Environment

Cooling Mode Temperature: $30 \pm 5(^{\circ}\text{C})$	27	Cooling Mode Humidity (%)	52
Heating Mode Temperature : $15 \pm 5(^{\circ}\text{C})$	20	Heating Mode Humidity (%)	56

Ñ Test Setup Description

The discontinuous disturbance measurement was performed with CLICK Analyzer to measure the click noise. The EUT configuration setup is shown in FIGURE 6 and 7, respectively. The testing method and the EUT setup were performed according to EN55014-1:2017.

The end of the power cord was connected to LISN at 80 cm. from the EUT. The ground connector of the LISN was connected to the ground of manufacturer.




FIGURE 6 - The test setup diagram.




FIGURE 7 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.3.2 Test Result

Measurement Port	AC Main			Operation Mode	A (See 3.1)
	Rx1 150KHz	Rx2 500KHz	Rx3 1.4MHz	Rx4 30MHz	
Short	0	0	0	0	
Long	0	0	0	0	
Fast Long (<020)	0	0	0	0	
Total Clicks	0	0	0	0	
Continuous Events	0	0	0	0	
Switch Op	0	0	0	0	
2 Click	0	0	0	0	
Continuous Time	0	0	0	0	
Limit dB μ V	55.9	55.9	55.9	55.9	
N	0.0	0.0	0.0	0.0	
Offsets	50dB	50dB	50dB	50dB	
Pass	0	0	0	0	
Duration of Test	20:02.8	20:02.8	20:02.8	20:02.8	
Limit dB μ V	89.9	89.9	89.9	89.9	
Allowed Clicks	0	0	0	0	
Remote	NONE				
Input Att.	0				
Extern. Att.	10 dB				
Rx1 150KHz	No Clicks				
Rx2 500KHz	No Clicks				
Rx3 1.4MHz	No Clicks				
Rx4 30MHz	No Clicks				
Status	PASS				

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

	Rx1 150KHz	Rx2 500KHz	Rx3 1.4MHz	Rx4 30MHz
Short	0	0	0	0
Long	0	0	0	0
Fast Long (<020)	0	0	0	0
Total Clicks	0	0	0	0
Continuous Events	0	0	0	0
Switch Op	0	0	0	0
2 Click	0	0	0	0
Continuous Time	0	0	0	0
Limit dB μ V	55.9	55.9	55.9	55.9
N	0.0	0.0	0.0	0.0
Offsets	50dB	50dB	50dB	50dB
Pass	0	0	0	0
Duration of Test	20:02.8	20:02.8	20:02.8	20:02.8
Limit dB μ V	89.9	89.9	89.9	89.9
Allowed Clicks	0	0	0	0
Remote	NONE			
Input Att.	0			
Extern. Att.	10 dB			
Rx1 150KHz	No Clicks			
Rx2 500KHz	No Clicks			
Rx3 1.4MHz	No Clicks			
Rx4 30MHz	No Clicks			
Status	PASS			

Result: Pass

Tested by: Marut Hninae

6.4 Test Item: Harmonic Emission

6.4.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
Signal Conditioning Unit	TESEQ	CCN1000-3	1347A01034	A2LA	20-02-19
AC-Power Source	TESEQ	NSG1007	1347A01034	-	20-02-19

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: ±3.85 %

Ñ Test Location: SR 1

Ñ Test Environment

Cooling Mode Temperature: 30 ±2(°C)	30	Cooling Mode Humidity (%)	55
Heating Mode Temperature :15 ± 2(°C)	20	Heating Mode Humidity (%)	54

Ñ Test Setup Description

The harmonic load currents were measured according to EN 61000-3-12:2012. The EUT was connected to AC power source, which was decoupled from the public mains connection. The analysis was performed with a measurement in a time domain of transient harmonic load currents. The data was transformed into a frequency range and assessed up to the 40th harmonic by using the Discrete Fourier Transforms. The EUT configuration for the harmonic current emission testing is shown in FIGURE 8 and 9, respectively.

Test Picture




FIGURE 8 - The setup diagram.



FIGURE 9 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

● Test Result

Measurement Port	AC Main	Operation Mode	A (See 3.1)
------------------	---------	----------------	-------------

THC/Iref (%): 22.0 Limit (%): 23.0 PWHC/Iref (%): 5.1 PWHC Limit (%): 23.0

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.021	1.202	1.8	0.037	1.803	2.1	Pass
3	3.099	3.246	95.5	3.169	4.869	65.1	Pass
4	0.013	0.601	2.1	0.022	0.902	2.4	Pass
5	0.652	1.608	40.6	0.699	2.412	29.0	Pass
6	0.007	0.401	1.7	0.015	0.601	2.6	Pass
7	0.822	1.082	76.0	0.865	1.623	53.3	Pass
8	0.009	0.301	2.9	0.015	0.451	3.2	Pass
9	0.256	0.571	44.8	0.277	0.857	32.3	Pass
10	0.007	0.240	2.8	0.011	0.361	3.2	Pass
11	0.327	0.466	70.2	0.353	0.699	50.5	Pass
12	0.006	0.200	3.1	0.012	0.301	3.8	Pass
13	0.216	0.301	71.9	0.242	0.451	53.7	Pass
14	0.005	N/A	N/A	0.010	N/A	N/A	N/A
15	0.201	N/A	N/A	0.212	N/A	N/A	N/A
16	0.004	N/A	N/A	0.008	N/A	N/A	N/A
17	0.024	N/A	N/A	0.041	N/A	N/A	N/A
18	0.003	N/A	N/A	0.006	N/A	N/A	N/A
19	0.100	N/A	N/A	0.120	N/A	N/A	N/A
20	0.003	N/A	N/A	0.006	N/A	N/A	N/A
21	0.082	N/A	N/A	0.111	N/A	N/A	N/A
22	0.003	N/A	N/A	0.005	N/A	N/A	N/A
23	0.067	N/A	N/A	0.081	N/A	N/A	N/A
24	0.003	N/A	N/A	0.005	N/A	N/A	N/A
25	0.056	N/A	N/A	0.070	N/A	N/A	N/A
26	0.003	N/A	N/A	0.006	N/A	N/A	N/A
27	0.047	N/A	N/A	0.056	N/A	N/A	N/A
28	0.003	N/A	N/A	0.006	N/A	N/A	N/A
29	0.047	N/A	N/A	0.056	N/A	N/A	N/A
30	0.003	N/A	N/A	0.007	N/A	N/A	N/A

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
31	0.090	N/A	N/A	0.107	N/A	N/A	N/A
32	0.005	N/A	N/A	0.010	N/A	N/A	N/A
33	0.117	N/A	N/A	0.135	N/A	N/A	N/A
34	0.005	N/A	N/A	0.010	N/A	N/A	N/A
35	0.087	N/A	N/A	0.104	N/A	N/A	N/A
36	0.004	N/A	N/A	0.009	N/A	N/A	N/A
37	0.088	N/A	N/A	0.106	N/A	N/A	N/A
38	0.004	N/A	N/A	0.008	N/A	N/A	N/A
39	0.091	N/A	N/A	0.117	N/A	N/A	N/A
40	0.005	N/A	N/A	0.009	N/A	N/A	N/A

Minimum Rsce required: Rsce = 31.604

Phase A = 95.8% of tested Rsce = 33.000, Rsce = 31.604

Measurement Port	AC Main	Operation Mode	D (See 3.1)
------------------	---------	----------------	-------------

THC/lref (%): 20.1 Limit (%): 23.0 PWHC/lref (%): 4.2 PWHC Limit (%): 23.0

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.023	1.329	1.8	0.045	1.994	2.2	Pass
3	3.115	3.588	86.8	3.164	5.383	58.8	Pass
4	0.013	0.665	2.0	0.026	0.997	2.6	Pass
5	0.746	1.778	42.0	0.773	2.666	29.0	Pass
6	0.007	0.443	1.6	0.016	0.665	2.4	Pass
7	0.758	1.196	63.4	0.776	1.794	43.3	Pass
8	0.009	0.332	2.7	0.014	0.498	2.8	Pass
9	0.285	0.631	45.1	0.304	0.947	32.1	Pass
10	0.006	0.266	2.2	0.011	0.399	2.7	Pass
11	0.395	0.515	76.6	0.416	0.773	53.9	Pass
12	0.006	0.222	2.5	0.010	0.332	3.1	Pass
13	0.184	0.332	55.4	0.232	0.498	46.5	Pass
14	0.005	N/A	N/A	0.008	N/A	N/A	N/A
15	0.190	N/A	N/A	0.203	N/A	N/A	N/A
16	0.004	N/A	N/A	0.009	N/A	N/A	N/A
17	0.048	N/A	N/A	0.061	N/A	N/A	N/A
18	0.003	N/A	N/A	0.007	N/A	N/A	N/A
19	0.105	N/A	N/A	0.117	N/A	N/A	N/A
20	0.003	N/A	N/A	0.005	N/A	N/A	N/A
21	0.074	N/A	N/A	0.115	N/A	N/A	N/A
22	0.002	N/A	N/A	0.006	N/A	N/A	N/A
23	0.081	N/A	N/A	0.092	N/A	N/A	N/A
24	0.002	N/A	N/A	0.005	N/A	N/A	N/A
25	0.075	N/A	N/A	0.100	N/A	N/A	N/A
26	0.002	N/A	N/A	0.005	N/A	N/A	N/A
27	0.061	N/A	N/A	0.070	N/A	N/A	N/A
28	0.003	N/A	N/A	0.006	N/A	N/A	N/A
29	0.067	N/A	N/A	0.074	N/A	N/A	N/A
30	0.003	N/A	N/A	0.007	N/A	N/A	N/A
31	0.127	N/A	N/A	0.139	N/A	N/A	N/A

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
32	0.004	N/A	N/A	0.008	N/A	N/A	N/A
33	0.131	N/A	N/A	0.146	N/A	N/A	N/A
34	0.004	N/A	N/A	0.008	N/A	N/A	N/A
35	0.104	N/A	N/A	0.126	N/A	N/A	N/A
36	0.004	N/A	N/A	0.009	N/A	N/A	N/A
37	0.088	N/A	N/A	0.099	N/A	N/A	N/A
38	0.004	N/A	N/A	0.009	N/A	N/A	N/A
39	0.115	N/A	N/A	0.133	N/A	N/A	N/A
40	0.004	N/A	N/A	0.008	N/A	N/A	N/A

Minimum Rsce required: Rsce = 28.805

Phase A = 87.3% of tested Rsce = 33.000, Rsce = 28.805

Result: Pass

Tested by: Marut Hninae

6.5 Test Item: Voltage Fluctuation

6.5.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
Signal Conditioning Unit	TESEQ	CCN1000-3	1347A01034	A2LA	20-02-19
Three Phase Impedance Network	TESEQ	INA2197	1347A01034	A2LA	20-02-19

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: $\pm 2.46\%$

Ñ Test Location: SR 1

Ñ Test Environment

Cooling Mode Temperature: $30 \pm 5(^{\circ}\text{C})$	30	Cooling Mode Humidity (%)	55
--	----	---------------------------	----

Ñ Test Setup Description

The Voltage fluctuation (flicker) was tested according to EN 61000-3-11:2001. The EUT was decoupled from the public main and connected to the reference impedance according to IEC 725. The voltage fluctuation testing was performed automatically with the Harmonic& Flicker Analyzer and the software. The EUT was operated continuously. The measurement was made after a steady state has been reached. The EUT configuration for the voltage fluctuation testing is shown in FIGURE 10 and 11, respectively.

Ñ Test Picture




FIGURE 10 - The setup diagram.



FIGURE 11 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.5.1 Test Result

Measurement Port	AC Main	Operation Mode	C (See 3.1)
------------------	---------	----------------	-------------

Maximum Flicker Results

T-max (mS):	0.0	Test limit (mS):	500.0	Pass
Highest dc (%):	1.08	Test limit (%):	3.30	Pass
Highest dmax (%):	1.15	Test limit (%):	4.00	Pass
Highest Pst (10 min. period):	0.204	Test limit:	1.000	Pass
Highest Plt (2 hr. period):	0.111	Test limit:	0.650	Pass

The maximum permissible system impedance Z_{sys}:

$$Z = 4.354 \text{ Ohm} + j 2.721 \text{ Ohm} \quad (4.354 \text{ Ohm} + 8661 \text{ mH})$$

Result: Pass

Tested by: Marut Hninae

6.6 Test Item: Electrostatic Discharge

6.6.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
ESD Generator	TESEQ	NSG438	1226	NIST	20-11-18

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: ± 7.09 %

Ñ Test Location: SR 1

Ñ Test Environment

Heating Mode Temperature : 15 ±5(°C)	16	Heating Mode Humidity (%)	55
--------------------------------------	----	---------------------------	----

Ñ Test Setup Description

The ESD was executed at a few weak points which can be normally touched by an operator or customer. The repetition rate between the impulses was at least 1 sec. The test points are shown in Figure 12.

The EUT configuration and diagram for the electrostatic discharge testing are shown in FIGURE 13 and 14 respectively. The parameters of the ESD generator and the critical test point are shown in above Table.

Electrostatic Discharge Testing Description

No.	Test Points	Type of Testing	Test Voltage (KV)	Number of Discharge per pol.	Operation Mode (see3.1)	Performance Criterion
1	A1-A5	Air	± 8	10	E	B
2	C6-C10	Contact	± 4	10	E	B
3	VCP	Contact	± 4	10	E	B

● Test Picture




FIGURE 12 Test points.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Test Picture




FIGURE 13 - The setup diagram.



FIGURE 14 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.6.2 Test Result.

(Heating mode)

Contact Discharge

Test Point	Test Execution							
	ESD Test Level (kV) / Number of Discharge (Times)							
	+ 2/10	- 2/10	+ 4/10	- 4/10	+ 8/10	- 8/10	+ 10/10	- 10/10
C6	-	-	ND	ND	-	-	-	-
C7	-	-	ND	ND	-	-	-	-
C8	-	-	ND	ND	-	-	-	-
C9	-	-	ND	ND	-	-	-	-
C10	-	-	ND	ND	-	-	-	-
VCP	-	-	NORM	NORM	-	-	-	-

Note: “-“ : Not Test

“ND” : Not Discharge

“NORM” : Normal

“AB” : Abnormal

Air Discharge

Test Point	Test Execution							
	ESD Test Level (kV) / Number of Discharge (Times)							
	+ 2/10	- 2/10	+ 4/10	- 4/10	+ 8/10	- 8/10	+ 10/10	- 10/10
A1	-	-	-	-	ND	ND	-	-
A2	-	-	-	-	ND	ND	-	-
A3	-	-	-	-	ND	ND	-	-
A4	-	-	-	-	ND	ND	-	-
A5	-	-	-	-	ND	ND	-	-

Note: “-“ : Not Test

“ND” : Not Discharge

“NORM” : Normal

“AB” : Abnormal

Phenomena Observed/Comments

-

Result: Pass

Tested by: Poomares Pomsri

6.7 Test Item: Electrical Fast Transient

6.7.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacturer	Model	S/N	Traceability	Due Date
EFT Simulator	TESEQ	NSG 3040/ CDN 3043/ FTM 3425-40	1943/2026/419	NIST	20-11-18
Capacitive Coupling Clamp	TESEQ	CDN 3425	1752	-	-

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: $\pm 5.03 \%$

Ñ Test Location: SR 1

Ñ Test Environment

Heating Mode Temperature : $15 \pm 5(^{\circ}\text{C})$	15	Heating Mode Humidity (%)	55
---	----	---------------------------	----

Ñ Test Setup Description

The EUT was arranged and connected to the auxiliary equipment for operating. For the power line testing, the coupling decoupling network (CDN) was used for coupling the EFT signal to the EUT's power line. For the control line testing, the capacitive coupling clamp (CCL) was used for coupling the EFT signal to the EUT's control line. The EUT configuration for the electrical fast transient testing is shown in FIGURE 15 and 16 respectively.

The Electrical Fast Transient Testing Descriptions

Test Line	Voltage	Port	Repetition Rate (kHz)	During Time (Sec/Polarity)	Performance criteria
L-G	$\pm 1 \text{ kV}$	AC	5	120	B
N-G	$\pm 1 \text{ kV}$	AC	5	120	B
PE-G	$\pm 1 \text{ kV}$	AC	5	120	B
L,N,PE-G	$\pm 1 \text{ kV}$	AC	5	120	B
Control Line	$\pm 0.5 \text{ kV}$	AC	5	120	B

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

Ñ Test Picture




FIGURE 15 - The setup diagram.



FIGURE 16 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.7.2 Test Result
(Heating mode)

Test Parameters			
Rise time :	5 ns	Period Time :	300 ms
Impulse Duration :	50 ns	Duration of Burst :	15 ms
Positive Burst :	2 min	Negative Burst :	2 min

Test Line	Voltage (kV)	Port	Repetition Rate (kHz)	During Time (Sec/Polarity)	Result
L-G	± 1 kV	AC	5	120	NORM
N-G	± 1 kV	AC	5	120	NORM
PE-G	± 1 kV	AC	5	120	NORM
L,N,PE-G	± 1 kV	AC	5	120	NORM
Control Line	± 0.5 kV	AC	5	120	NORM

Note: “-“: Not Test “NORM”: Normal “AB”: Abnormal

Phenomena Observed/Comments
-

Result: Pass

Tested by: MR. Poomares Pomsri

6.8 Test Item: Surge

6.8.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
Surge Simulator	TESEQ	NSG3040/ CDN 3043/ CWM 3450-40	1943/2026/1093	NIST	20-11-18

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: ± 6.78 %

Ñ Test Location: SR 1

Ñ Test Environment

Heating Mode Temperature :15 ±5(°C)	16	Heating Mode Humidity (%)	55
-------------------------------------	----	---------------------------	----

Ñ Test Setup Description

The EUT was placed on the 10 cm height isolator above the ground reference plane. The EUT was arranged and connected to the auxiliary equipment for operating. The distance from the EUT to the other conductive materials was more than 1 m.

For the Surge testing of the power line, the CDN (coupling decoupling network) was used for coupling the surge to the EUT. The AC power cord between EUT and CDN was 1 m. The EUT configuration for the surge immunity testing is shown in FIGURE 17 and 18 respectively.

Surge Testing Description

Voltage (kV)	Test Point	Port	Number of apply Per polarity	Phase angle	Performance criteria
±1	L-N	AC	5	0°,90°, 270°	B
±2	L-PE, N-PE	AC	5	0°,90°, 270°	B

Test Picture




FIGURE 17 - The setup diagram.



FIGURE 18 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.8.2 Test Result

Test Parameters									
Wave Form:	1.2/50 μ S	Generator Source Impedance:	2 Ω	Surge Repetition Rate:	1Pulse/min				

Coupling Mode	Phase	+ 0.5 kV	- 0.5 kV	+ 1 kV	- 1 kV	+ 2 kV	- 2 kV	+ 4 kV	- 4 kV
L-N	0°,90°, 270°	-	-	NORM	NORM	-	-	-	-

Note: “-”: Not Test “NORM”: Normal “AB”: Abnormal

Test Parameters									
Wave Form:	1.2/50 μ S	Generator Source Impedance:	12 Ω	Surge Repetition Rate:	1Pulse/min				

Coupling Mode	Phase	+ 0.5 kV	- 0.5 kV	+ 1 kV	- 1 kV	+ 2 kV	- 2 kV	+ 4 kV	- 4 kV
L-PE	0°,90°, 270°	-	-	-	-	NORM	NORM	-	-
N-PE	0°,90°, 270°	-	-	-	-	NORM	NORM	-	-

Note: “-”: Not Test “NORM”: Normal “AB”: Abnormal

Phenomena Observed/Comments
-

Result: Pass

Tested by: Poomares Pomsri

6.9 Test Item: Conducted Immunity

6.9.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
EM clamp	TESEQ	KEMZ 801AS50	38662	TESEQ	14-05-18
Compact immunity test system	TESEQ	NSG 4070B-30	39604	DKD	04-05-18
Dual directional coupler	TESEQ	DCP 0100A	40093	TESEQ	04-05-18
Power Amplifier	TESEQ	CBA400M-110	T44431	TESEQ	20-05-18
Current injection probe	TESEQ	CIP 9136A	35442	TESEQ	15-05-18
Coupling/Decoupling network	TESEQ	CDN M332S	37751	TESEQ	14-05-18

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: ± 2.09 dB

Ñ Test Location: SR 1

Ñ Test Environment

Heating Mode Temperature :15 ± 2(°C)	20	Heating Mode Humidity (%)	54
--------------------------------------	----	---------------------------	----

Ñ Test Setup Description

The EUT was set up according to IEC61000-4-6:2013 (Ed 3.0). The conducted interference signal was connected to the 6 dB attenuator before connected to the CDN and the EM-Clamp for injecting the RF signal to the EUT at the power cord and the signal line respectively. The test setup diagram and the test setup picture are shown in the FIGURE 19 and 20.

Ñ Test Picture




FIGURE 19 - The setup diagram.



FIGURE 20 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.9.2 Test Result
(Heating mode)

Test port	Test level	Frequency	Step frequency	Modulation	Dwell time	Result
AC Power Line	3 V	150 KHz-230 MHz	1% Log	AM 80% with 1kHz	3 Sec	NORM
Control Line	1 V	150 KHz-230 MHz	1% Log	AM 80% with 1kHz	3 Sec	NORM

Note: “-”: Not Test

“NORM”: Normal

“AB”: Abnormal

Phenomena Observed/Comments

-

Result: Pass

Tested by: MR. Poomares Pomsri

6.10 Test Item: Voltage Dips

6.10.1 Test Setup

Ñ Test Specification

See 1 and 2.1

Ñ Test Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
PQF Simulator	TESEQ	NSG 3041/ PQM 3403/ INA 6501	1943/1035/223	NIST	20-11-18

Ñ Customer's Equipment

Equipment Name	Manufacture	Model	S/N	Traceability	Due date
-	-	-	-	-	-

Ñ Test Uncertainty: ± 3.17%

Ñ Test Location: SR 1

Ñ Test Environment

Heating Mode Temperature :15 ±5(°C)	16	Heating Mode Humidity (%)	54
-------------------------------------	----	---------------------------	----

Ñ Test Setup Description

The power cord of the EUT was connected to the voltage dip and the interruption generator. The EUT was arranged and connected to the auxiliary equipment for operating.

The EUT configuration for the voltage dip and the short interruption testing are shown in FIGURE 21 and 22 respectively.

The voltage dip and the interruption testing descriptions

Phenomena	Test Level in% (ut)	Cycle	Phase angle	Performance criteria
V. Dip	40	0.5	0°	C
V. Dip	70	10	0°	C
Interruption	100	25	0°	C

Ñ Test Picture




FIGURE 21 - The setup diagram.



FIGURE 22 - The test setup picture.

This test report is test results from the EUT only, not the product's quality certificate. It shall not be reproduced except in full without the written approval of testing laboratory.

6.10.2 Test Result

Test Phenomena	Number of Test	I/P Voltage / Frequency	Test Level in% (ut)	Phase angle (°)	Cycle	Result
V. Dip	3	230 V/50Hz	40	0°	0.5	NORM
V. Dip	3	230 V/ 50Hz	70	0°	10	NORM
Interruption	3	230 V/ 50Hz	100	0°	25	NORM

Note: “-“ : Not Test

“NORM” : Normal

“AB” : Abnormal

Phenomena Observed/Comments

-

Result: Pass

Tested by: Poomares Pomsri

----- End of Report -----