QUIET ALTERNATIVE

Seiya NEW





Highlights

BASIC Line compact inverter A++ in cooling & heating mode Dust filter and Ultra-Fresh filter Infrared remote control included - WiFi ready

































Compact highwall unit from the BASIC line SEIYA with standard air filter. For use with 1:1 single outdoor unit or in combination with other indoor units on a 2- to 5-room multi outdoor unit.



Product Advantages

- Excellent energy efficiency (A+ to A++)
- Colored, dimmable LED displays
- Wired connection option for IR remote control
- Low GWP refrigerant R32
- Air used as energy source in heating operation
- Compact outdoor and indoor units
- _ Whisper mode



Clean ambient air

- Washable dust filter that covers the entire heat exchanger
- _ Ultra Fresh filter strips: neutralize up to 99.9% of bacteria and viruses; deodorizing effect against odors; 85% effective against PM2.5 fine dust particles
- Dustless coil coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation
- Optional active carbon-catechin filter strips
- Optional IAQ filter strips
- Optional Ultra Pure 2.5 filter strips



Easy operation

- Infrared remote control included
- _ WiFi ready
- Optional APP control via smartphone or tablet
- _ 24 hour ON/OFF timer
- Automatic mode
- PRESET memory function
- _ Hi Power
- QUIET function for indoor unit
- SILENT function for outdoor unit, 2-stage
- _ Louver swing & fix
- 8°C frost protection function
- Automatic restart after power blackout



WiFi special features

- All indoor units & groups on/off control
- _ All indoor units & groups weekly timer
- _ All indoor units & groups setting
- Indoor temperature display
- Outdoor temperature display
- Power select
- _ Child lock
- _ ECO operating mode
- Fireplace operating mode
- _ Hi Power operating mode
- _ Energy Monitoring



Seiya NEW / SET

| Indoor unit | | | RAS-24E2KVG-E |
|---|-------|---|----------------|
| Outdoor unit | | | RAS-24E2AVG-E |
| Cooling capacity | kW | * | 6,50 |
| Cooling range (minmax.) | kW | * | 1,70 - 7,20 |
| Power consumption (min./nom./max.) | kW | * | 0,41/2,25/2,60 |
| Pdesign c | kW | | 6,50 |
| Energy efficiency EER | W/W | * | 2,89 |
| Energy efficiency SEER | | * | 6,90 |
| Energy efficiency class | | * | A++ |
| Annual electricity consumption | kWh/a | * | 330 |
| Outdoor temperature operating range (minmax.) | °C | * | -15/+46 |
| Heating capacity | kW | * | 7,00 |
| Heating range (minmax.) | kW | * | 1,50 - 8,10 |
| Power consumption (min./nom./max.) | kW | * | 0,29/2,10/2,55 |
| Pdesign h | kW | | 5,40 |
| Energy efficiency COP | W/W | * | 3,33 |
| Energy efficiency SCOP | | * | 4,30 |
| Energy efficiency class | | * | A+ |
| Annual electricity consumption | kWh/a | * | 1757 |
| Outdoor temperature operating range (minmax.) | °C | * | -15/+24 |

| Indoor unit | | | RAS-24E2KVG-E |
|-------------------------------------|-------|---|------------------|
| Sound pressure level (low/med/high) | dB(A) | * | 29//48 |
| Sound pressure level (low/med/high) | dB(A) | * | 29//48 |
| Sound power level | dB(A) | * | 61 |
| Sound power level | dB(A) | * | 61 |
| Airflow | m³/h | | 1070 |
| Condensate pipe diameter | mm | | VP13 |
| Dimensions (HxWxD) | mm | | 320 x 1050 x 250 |
| Weight | kg | | 15 |

☆ Cooling → Heating



Seiya NEW / SET

| Outdoor unit | | | RAS-24E2AVG-E |
|-------------------------------------|-----------|---|-----------------|
| Power supply | V/Ph+N/Hz | | 220-240/1/50 |
| Recommended fusing | А | | 16 |
| Recommended power supply line type | | | H07RN-F 3G1,5 |
| Communication line | | | H07RN-F 4G1,5 |
| Sound pressure level (low/med/high) | dB(A) | * | //54 |
| Sound pressure level (low/med/high) | dB(A) | * | //54 |
| Sound power level | dB(A) | * | 67 |
| Sound power level | dB(A) | * | 67 |
| Suction gas pipe diameter | mm (inch) | | 12,7 (1/2) |
| Liquid pipe diameter | mm (inch) | | 6,3 (1/4) |
| Pipe length (min.) | m | | 2 |
| Pipe length (max.) | m | | 20 |
| Pipe length/indoor unit (min.) | m | | 2 |
| Height difference (max.) | m | | 15 |
| Airflow | m³/h | | 2220 |
| Compressor type | | | Twin Rotary |
| Refrigerant | | | R32 |
| Refrigerant charge | kg | | 1,18 |
| Pre-charged up to | m | | 15 |
| Added refrigerant charge | g/m | | 20 |
| Dimensions (HxWxD) | mm | | 550 x 780 x 290 |
| Weight | kg | | 38 |

^{*} Cooling Heating

 $The \ measuring \ conditions \ for \ this \ product \ can \ be \ found \ at \ https://www.toshiba-aircondition.com/en/measuring-conditions.html$

| Accessories | Description |
|---------------|---|
| Fernbedienung | Infrared remote control included |
| RB-RXS33-E | Infrared remote control including weekly timer and 8°C frost protection function |
| RB-RXS34-E | HAORI design infrared remote control, black, with magnetic holder |
| RB-N105S-G | TOSHIBA Home AC control - wireless WiFi control / Seiya, Shorai Edge, Daiseikai 9 |
| 818F0036 | IAQ filter strips |
| 818F0023 | Active carbon-catechin filter strips |
| 818F0072 | Ultra-Fresh filter strips |
| TCB-IFCB5-PE | External on/off PCB, window contact module |
| TCB-PX100-PE | Casing for outdoor installation of window contact module for high-wall units |



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



Energy Label A++: Energy efficiency class A++ guarantees a very low power consumption.



Hybrid inverter control: Smooth capacity regulation.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



R32: Used refrigerant: R32.



Wifi ready: WiFi adapter optional.



Dust filter: Washable filter against coarse contamination.



Self-cleaning function: Usage of condensate water for cleaning.



Auto Mode: Automatic selection between cooling and heating.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Auto diagnostic: Check of system for flawless operation.



Eco Mode: Energy saving function.



Quiet Mode: Whisper mode for the indoor unit.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



Preset Mode: Activates individual settings at the touch of a button



Timer: Individual programming of on-/off times.



Automatic Restart: After a power blackout.



8°C Antifreeze Protection: Protects unoccupied rooms.

