



BASIC-LINE WORKHORSE

Digital Inverter CLASSIC R32



Highlights

- Economy RAV Inverter - 100% TOSHIBA
- Compact, light & quiet
- Twin-rotary compressor

Digital Inverter CLASSIC outdoor unit for RAV single-room systems with refrigerant R32 for cooling or heating with a wide performance spectrum. Available in five capacity levels from 5.0 to 13.0 kW. For 1:1 combination with 4-way Standard Cassettes, Standard Duct units or Highwall units of the RAV-HM (SL) series.



Performance

- Suitable for 24/7 continual operation
- High energy efficiency (up to A++)
- SEER values up to 6.2 possible depending on the combination
- SCOP values up to 4.2 possible depending on the combination
- Exceptionally high efficiency in the partial load range
- Controls at the lowest, min. capacities
- Corresponds to the ECODESIGN Lot 10 Directive



Flexibility

- Max. piping length 30 m for all units
- Max. height differences up to 30 m
- Flexible control options
- Wide operating temperature range from -15 to +46 °C



Technical details

- Direct current hybrid inverter technology
- All units 1-phase, 230 V available
- Capacity sizes of 10, 12, 13 kW alternative 3-phase, 400V available
- Inspection window simplifies maintenance
- Quiet! Night Operation programmable via wired Remote Control
- Save Operation setting for requirement limitation of 50% to 100%



Digital Inverter CLASSIC R32

Technical data			RAV-GV561ATP-E
Cooling capacity	kW	❄️	5,00
Cooling range (min.-max.)	kW	❄️	1,50 - 5,60
Outdoor temperature operating range (min.-max.)	°C	❄️	-15/+46
Heating capacity	kW	🔥	5,30
Heating range (min.-max.)	kW	🔥	1,50 - 6,30
Outdoor temperature operating range (min.-max.)	°C	🔥	-15/+15
Capacity code	HP		2
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	🔥	48
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	65
Suction gas pipe diameter	mm (inch)		12,7 (½)
Liquid pipe diameter	mm (inch)		6,3 (¼)
Pipe length (min.)	m		5
Pipe length (max.)	m		20
Height difference (max.)	m		20
Airflow	m³/h		2400
Power supply	V/Ph+N/Hz		220-240/1N/50
Recommended fusing	A		16
Recommended power supply line type			H07RN-F 3G2,5
Communication line			H07RN-F 4G1,5
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		0,90
Pre-charged up to	m		20
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		36

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

