TOSHIBA

QUIET ALTERNATIVE

Seiya NEW





Highlights

BASIC Line compact inverter A++ in cooling & heating mode Dust filter and Ultra-Fresh filter Infrared remote control included – WiFi ready

Compact highwall unit from the BASIC line SEIYA with standard air filter. For use with 1:1 single outdoor unit or in combination with other indoor units on a 2- to 5-room multi outdoor unit.



Product Advantages

- Excellent energy efficiency (A+ to A++)
- Colored, dimmable LED displays
- Wired connection option for IR remote control
- Low GWP refrigerant R32
- Air used as energy source in heating operation
- Compact outdoor and indoor units
- _ Whisper mode



Clean ambient air

- Washable dust filter that covers the entire heat exchanger
- Ultra Fresh filter strips: neutralize up to 99.9% of bacteria and viruses; deodorizing effect against odors; 85% effective against PM2.5 fine dust particles
- Dustless coil coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation
- Optional active carbon-catechin filter strips
- Optional IAQ filter strips
- Optional Ultra Pure 2.5 filter strips

\longrightarrow

Easy operation

- Infrared remote control included
- WiFi ready
- Optional APP control via smartphone or tablet
- _ 24 hour ON/OFF timer
- _ Automatic mode
- PRESET memory function
- _ Hi Power
- QUIET function for indoor unit
- SILENT function for outdoor unit, 2-stage
- Louver swing & fix
- 8°C frost protection function
- Automatic restart after power blackout



WiFi special features

- _ All indoor units & groups on/off control
- All indoor units & groups weekly timer
- All indoor units & groups setting
- Indoor temperature display
- Outdoor temperature display
- _ Power select
- Child lock
- _ ECO operating mode
- Fireplace operating mode
- Hi Power operating mode
- _ Energy Monitoring



Symbol photo

TOSHIBA

Seiya NEW / SET

Indoor unit			RAS-B24E2KVG-E
Outdoor unit			RAS-24E2AVG-E
Cooling capacity	kW	*	6,50
Cooling range (minmax.)	kW	*	1,70 - 7,20
Power consumption (min./nom./max.)	kW	*	0,41/2,25/2,60
Pdesign c	kW		6,50
Energy efficiency EER	W/W	*	2,89
Energy efficiency SEER		*	6,90
Energy efficiency class		*	A++
Annual electricity consumption	kWh/a	*	330
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	*	7,00
Heating range (minmax.)	kW	*	1,50 - 8,10
Power consumption (min./nom./max.)	kW	*	0,29/2,10/2,55
Pdesign h	kW		5,40
Energy efficiency COP	W/W	*	3,33
Energy efficiency SCOP		*	4,30
Energy efficiency class		*	A+
Annual electricity consumption	kWh/a	*	1757
Outdoor temperature operating range (minmax.)	°C	*	-15/+24

Indoor unit			RAS-B24E2KVG-E
Sound pressure level (low/med/high)	dB(A)	*	29//48
Sound pressure level (low/med/high)	dB(A)	*	29//48
Sound power level	dB(A)	*	61
Sound power level	dB(A)	*	61
Airflow	m³/h		1070
Condensate pipe diameter	mm		VP13
Dimensions (HxWxD)	mm		320 x 1050 x 250
Weight	kg		15

☆ Cooling → Heating



TOSHIBA

Seiya NEW / SET

Outdoor unit			RAS-24E2AVG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	А		16
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Sound pressure level (low/med/high)	dB(A)	*	//54
Sound pressure level (low/med/high)	dB(A)	*	//54
Sound power level	dB(A)	*	67
Sound power level	dB(A)	*	67
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Pipe length/indoor unit (min.)	m		2
Height difference (max.)	m		15
Airflow	m³/h		2220
Compressor type			Twin Rotary
Refrigerant			R32
Refrigerant charge	kg		1,18
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		38

^{*} Cooling Heating

 $The \ measuring \ conditions \ for \ this \ product \ can \ be \ found \ at \ https://www.toshiba-aircondition.com/en/measuring-conditions.html$

Accessories	Description
Fernbedienung	Infrared remote control included
RB-N105S-G	TOSHIBA Home AC control - wireless WiFi control / Seiya, Shorai Edge, Daiseikai 9

