VERSATILE ALLROUNDER

SHORAI EDGE





Highlights

Perfect allrounder with Careflow A +++ for cooling & heating - 3D Airflow (18, 22, 24) Ultra Pure 2.5 filter







































Stylish hiwall unit in a seamless matt design. Highest energy efficiency in combination with Ultra-Pure air filter and comfort remote control. 3D- and Careflow- air distribution move the air flow draft-free in the room.



Attractive and economical

- Very high energy efficiency (A +++)
- DC Hybrid inverter technology
- Particularly high efficiency in part load range
- _ Whisper mode for indoor & outdoor units
- Colored, dimmable LED displays
- Infrared remote control can be used as a cable remote control
- _ draft-free comfort: 3D Airflow (18, 22, 24)
- intelligent airflow: Hada Careflow



Resource-friendly

- Inverter control minimizes power consumption
- _ ECO mode
- _ Air as an energy source in heating mode
- _ Low-GWP refrigerant R32



Clean ambient air

- Washable dust filters cover the entire heat exchanger
- "Magic Coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after the end of operation
- $_{-}$ Highly effective Ultra Pure filter of the particle class 2.5 μ



- Comfort infrared remote control included
- _ Clear & simple operation
- Automatic mode, Hi power, Preset
- _ Comfort sleep
- Weekly timer with 4 freely programmable settings / day
- _ 28 time programs per week
- QUIET mode for indoor unit
- SILENT mode for outdoor unit
- _ 8 ° C frost protection function
- _ Fireplace mode
- Power Select
- Automatic restart after power failure adjustable
- Optional APP control via smartphone and tablet
- _ WIFI module can be integrated in the indoor unit
- $_{\rm -}$ An indoor unit can be operated by up to 5 users
- Up to 10 indoor units can be controlled by one user
- Several devices can be combined in up to 3 groups / zones
- _ Child lock
- Multi-Language APP: German, English, Czech, Croatian, Hungarian, Slovenian, Slovak



SHORAI EDGE / SET

Indoor unit			RAS-B10J2KVSG-E
Outdoor unit			RAS-10J2AVSG-E1
Cooling capacity	kW	*	2,50
Cooling range (minmax.)	kW	*	0,89 - 3,20
Power consumption (min./nom./max.)	kW	*	0,19/0,54/0,79
Pdesign c	kW		2,5
Energy efficiency EER	W/W	*	4,63
Energy efficiency SEER		*	8,60
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	*	102
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	*	3,20
Heating range (minmax.)	kW	*	0,90 - 4,80
Power consumption (min./nom./max.)	kW	*	0,16/0,70/1,23
Pdesign h	kW		2,5
Energy efficiency COP	W/W	*	4,57
Energy efficiency SCOP		*	5,10
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	*	686
Outdoor temperature operating range (minmax.)	°C	*	-15/+24

Indoor unit			RAS-B10J2KVSG-E
Sound pressure level (low/med/high)	dB(A)	*	19/22/40
Sound pressure level (low/med/high)	dB(A)	*	19/23/40
Sound power level	dB(A)	*	53
Sound power level	dB(A)	*	53
Airflow	m³/h		312-660
Condensate pipe diameter	mm		16
Dimensions (HxWxD)	mm		293 x 800 x 226
Weight	kg		10

* Cooling Heating



SHORAI EDGE / SET

Outdoor unit			RAS-10J2AVSG-E1
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	А		10
Communication line			H07RN-F 4G1,5
Current consumption (nom.)	А		2,45
Current consumption (max.)	А		3,65
Sound pressure level (low/med/high)	dB(A)	*	37/43/44
Sound pressure level (low/med/high)	dB(A)	*	39/45/46
Sound power level	dB(A)	*	57
Sound power level	dB(A)	*	59
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m³/h		1890
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,55
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		26

^{*} Cooling * Heating

 $The \ measuring \ conditions \ for \ this \ product \ can \ be \ found \ at \ https://www.toshiba-aircondition.com/en/measuring-conditions.html$

Accessories	Description
Fernbedienung	Infrared remote control included
RB-N103S-G	TOSHIBA Home AC control - wireless WiFi control / Seiya (24), Shorai Edge, Daiseikai 9
818F0036	IAQ filter strips
818F0023	Active carbon-catechin filter strips
818F0050	Ultra-pure 2.5 filter strips
TCB-IFCB5-PE	External on/off PCB, window contact module
TCB-PX100-PE	Casing for outdoor installation of window contact module for high-wall units



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



Energy Label A+++: Energy efficiency class **A+++** guarantees the lowest power consumption and the highest efficiency!



Hybrid inverter control: Smooth capacity regulation.



Rotary compressor: Reliability and high efficiency.



R32: Used refrigerant: R32.



Wifi ready: WiFi adapter optional.



Dust filter: Washable filter against coarse contamination.



Self-cleaning function: Usage of condensate water for cleaning.



Auto Mode: Automatic selection between cooling and heating.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Auto diagnostic: Check of system for flawless operation.



Eco Mode: Energy saving function.



Quiet Mode: Whisper mode for the indoor unit.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



Preset Mode: Activates individual settings at the touch of a button.



Timer: Individual programming of on-/off times.



Week Timer: Up to four settings per day and seven per week.



Automatic Restart: After a power blackout.



8°C Antifreeze Protection: Protects unoccupied rooms.

