TOSHIBA

UNIVERSAL ALLROUNDER

SHORAI EDGE B&W



HIGH line hiwall unit in a seamless matt design, optionally in classic white or in stylish black. Highest energy efficiency in combination with Ultra-Pure air filter and design remote control. 3D- and Careflow- air distribution move the air flow draft-free in the room. For use with 1:1 single outdoor unit or in combination with other indoor units on a 2 to 5 room multi outdoor unit.



Attractive and economical

- Very high energy efficiency (A +++)
- DC Hybrid inverter technology
- Particularly high efficiency in part load range
- Whisper mode for indoor & outdoor units
- Colored, dimmable LED displays
- _ Draft-free comfort: 3D Airflow (18, 22, 24)
- Intelligent airflow: Hada Careflow



Resource-friendly

- Inverter control minimizes power consumption
- _ ECO mode
- Air as an energy source in heating mode
- Low-GWP refrigerant R32



Clean ambient air

- Washable dust filters cover the entire heat exchanger
- "Magic Coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after the end of operation
- $_{-}$ Highly effective Ultra Pure filter of the particle class 2.5 μ

Operation & features

- Design infrared remote control included
- Clear & simple operation
- Automatic mode, Hi power
- OFF-timer (1 to 12 hours)
- QUIET mode for indoor unit
- SILENT mode for outdoor unit
- $_{-}$ 8 ° C frost protection function
- _ Fireplace mode
- Power Select
- Automatic restart after power failure adjustable
- APP control via smartphone and tablet
- WIFI module integrated in the indoor unit as standard
- An indoor unit can be operated by up to 5 users
- $_{\rm -}$ Up to 10 indoor units can be controlled by one user
- Several devices can be combined in up to 3 groups / zones
- _ Child lock
- Multi-Language APP: German, English, Czech, Croatian, Hungarian, Slovenian, Slovak
- ENERGY MONITORING makes the power consumption transparent.



TOSHIBA

SHORAI EDGE B&W / SET

Indoor unit			RAS-B10G3KVSG-E
Outdoor unit			RAS-10J2AVSG-E1
Cooling capacity	kW	*	2,50
Cooling range (minmax.)	kW	*	0,89 - 3,20
Power consumption (min./nom./max.)	kW	*	0,19/0,54/0,79
Pdesign c	kW		2,5
Energy efficiency EER	W/W	*	4,63
Energy efficiency SEER		*	8,60
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	*	102
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	*	3,20
Heating range (minmax.)	kW	*	0,90 - 4,80
Power consumption (min./nom./max.)	kW	*	0,16/0,70/1,23
Pdesign h	kW		2,50
Energy efficiency COP	W/W	*	4,57
Energy efficiency SCOP		*	5,10
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	*	686
Outdoor temperature operating range (minmax.)	°C	*	-15/+24

Indoor unit			RAS-B10G3KVSG-E
Sound pressure level (low/med/high)	dB(A)	*	19/22/40
Sound pressure level (low/med/high)	dB(A)	*	19/-/40
Sound power level	dB(A)	*	53
Sound power level	dB(A)	*	53
Airflow	m³/h		312-660
Condensate pipe diameter	mm		16
Dimensions (HxWxD)	mm		293 x 800 x 226
Weight	kg		10

* Cooling Heating



TOSHIBA

SHORAI EDGE B&W / SET

Outdoor unit			RAS-10J2AVSG-E1
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	А		10
Communication line			H07RN-F 4G1,5
Current consumption (nom.)	А		2,45
Current consumption (max.)	А		3,65
Sound pressure level (low/med/high)	dB(A)	*	36/43/44
Sound pressure level (low/med/high)	dB(A)	*	38/44/46
Sound power level	dB(A)	*	-/-/57
Sound power level	dB(A)	*	-/-/59
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m³/h		1890
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,55
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		26

^{*} Cooling Heating

 $The \ measuring \ conditions \ for \ this \ product \ can \ be \ found \ at \ https://www.toshiba-aircondition.com/en/measuring-conditions.html$

Accessories	Description
Fernbedienung	Infrared remote control included

